KEL-FG-ER | Split flange enclosure

for 90° feed-in of cables with connectors / IP65

















The cable entry frames KFI-FG-FR are suited for installation of cables with connectors and conduits at an angle of 90° to the cabinet, enclosure or machine wall, providing an IP65 rating and strain relief for cable diameters from 1 to 16 mm (single-hole grommets KT 1 - 15) and 13 to 35 mm (single-hole grommets KTG 13 - KT 34).

The KEL-FG-ER-A frame matches exactly the cut-out dimensions for 24-pin standard industrial connectors. The KEL-FG-ER-B is suited for cut-outs 36 \times 46

The single-row versions KEL-FG-ER-E are particularly suited for flat connectors. The small frames are ideal for applications with limited space.

Due to the integrated seal on the flange enclosure, a protection class of up to IP65 is provided. An additional flat rubber gasket is included in the shipment.

It is also possible to integrate threaded bushings. Please ask us about your desired variant.

The version with threaded bushings enables the cable entry frame to be screwed onto the housing from the inside out. This protects against vandalism and tampering with the housing from the outside.

Specifications

IP rating (EN 60529)	IP54, IP55, IP64, IP65
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 90 C°
Properties	vibration proof, UV-resistant, silicone free, halogen free
Mounting options	Screw type mounting
Mounting height	57,5 mm

Advantages & benefits

Integrated seal

Protection class IP65 acc. to EN 60529

Installation at an angle of 90° to the wall

Mechanical protection of the cable directly at the place of entry

Protection against water splashes and drips

Ideal for cables with connectors (max. Ø 35 mm)

Strain relief according to EN 62444

High flexibility when using the IMAS-CONNECT™ system

Product types & sizes

KEL-FG-ER-A10

Part No. Package quantity For max. no. of cables Max. cable diameter Lenath

42340 4251269328787 1 10 16 mm 147 mm Width 80 mm

Height Mounting height

Cut-out size No. of screw holes Diam. of screw holes Screw material

57,5 mm 57,5 mm 112 × 36 mm 5,5 mm

Mild steel, galvanically zinc

plated

10 x KT small Suitable for grommets

KEL-FG-ER-A7

Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material

57,5 mm 57,5 mm 112 × 36 mm 5.5 mm

Mild steel, galvanically zinc plated

Suitable for grommets 6 x KT small 1 x KT large

KEL-FG-ER-A4	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42342 4251269328800 1 4 35 mm 147 mm 80 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	57,5 mm 57,5 mm 112 × 36 mm 4 5,5 mm Mild steel, galvanically zinc plated 2 x KT small 2 x KT large
KEL-FG-ER-B4	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42344 4251269328824 1 4 16 mm 79,8 mm 80 mm	Height Mounting height No. of screw holes Diam. of screw holes Screw material Suitable for grommets	57,5 mm 57,5 mm 4 5,5 mm Mild steel, galvanically zinc plated 4 x KT small
KEL-FG-ER-B1	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42343 4251269328817 1 1 35 mm 79,8 mm 80 mm	Height Mounting height No. of screw holes Diam. of screw holes Screw material Suitable for grommets	57,5 mm 57,5 mm 4 5,5 mm Mild steel, galvanically zinc plated 1 x KT large
KEL-FG-ER-E5	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42347 4251269328855 5 5 17 mm 147 mm 53 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	38 mm 38 mm 112 × 24 mm 2 5,5 mm Mild steel, galvanically zinc plated 5 x KT small
KEL-FG-ER-E3	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42346 4251269328848 5 3 17 mm 100 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	38 mm 38 mm 65 × 24 mm 2 5,5 mm Mild steel, galvanically zinc plated 3 x KT small
KEL-FG-ER-E2	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42345 4251269328831 5 2 17 mm 73 mm 53 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	38 mm 38 mm 43 × 24 mm 2 5,5 mm Mild steel, galvanically zinc plated 2 x KT small

R

