

KEL-QTA | Pluggable cable entry plates

for cables with connectors, tool-free assembly / IP54



IP54

Made in Germany

C_{UL}US

RoHS compliant

RIIA

REACH COMPLIANCE

HL3

EN 45545-2

ECOLAB

certified

UV

ISO 4892-2A

Split, pluggable cable entry plates (IP54) for routing pre-terminated and standard cables utilising [split QT grommets](#) or membranes.

Suitable for cut-outs for 10- and 24-pin industrial connectors. The compact size KEL-QTA-B is suitable for cut-outs 45.5 x 45.5 mm. The round versions of the KEL-QTA are suitable for cut-outs 32 / 50 mm in diameter.

The KEL-QTA easily routes pre-terminated cables, multi-conductors, hoses or conduits without using any tools for assembly.

Specifications

IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	UV-resistant, silicone free, halogen free
Mounting options	Snap-in
Mounting height	5 mm

Advantages & benefits

- Quick assembly without tools
- High cable density
- Routing of cables with and without connectors
- Upon disassembly (e.g. maintenance) screwing and unscrewing of the cable entry frame is not necessary
- Available for a large range of cut-out sizes
- Suitable for metric cut-outs
- Greatly increased cable density when using double or quadruple grommets

Product types & sizes

KEL-QTA 24 4 A 	Part No.	43644	Height	12 mm
	EAN	4251269310379	Mounting height	5 mm
	Package quantity	10	Cut-out size	112 x 36 mm
	For max. no. of cables	16	For min. wall thickness	1,5 mm
	Max. cable diam., with connector	15 mm	For max. wall thickness	2,5 mm
	Length	142 mm	For wall thickness	1,5 - 2,5 mm
	Width	44 mm	Suitable for grommets	4 x QT small
KEL-QTA 24 4 B 	Part No.	43645	Height	12 mm
	EAN	4251269310386	Mounting height	5 mm
	Package quantity	10	Cut-out size	112 x 36 mm
	For max. no. of cables	16	For min. wall thickness	2,8 mm
	Max. cable diam., with connector	15 mm	For max. wall thickness	4 mm
	Length	142 mm	For wall thickness	2,8 - 4 mm
	Width	44 mm	Suitable for grommets	4 x QT small

KEL-QTA24|2-DP 18 A




Part No.	43642	Width	44 mm
EAN	4251269310355	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	26	Cut-out size	112 × 36 mm
Max. cable diam., with connector	15 mm	For min. wall thickness	1,5 mm
Max. cable diam., without connector	16 mm	For max. wall thickness	2,5 mm
Length	142 mm	For wall thickness	1,5 - 2,5 mm
		Suitable for grommets	2 x QT small

KEL-QTA24|2-DP 18 B




Part No.	43643	Width	44 mm
EAN	4251269310362	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	26	Cut-out size	112 × 36 mm
Max. cable diam., with connector	15 mm	For min. wall thickness	2,8 mm
Max. cable diam., without connector	16 mm	For max. wall thickness	4 mm
Length	142 mm	For wall thickness	2,8 - 4 mm
		Suitable for grommets	2 x QT small

KEL-QTA 10|2-DP 6 A




Part No.	43656	Width	44 mm
EAN	4251269310409	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	14	Cut-out size	65 × 36 mm
Max. cable diam., with connector	15 mm	For min. wall thickness	1,5 mm
Max. cable diam., without connector	5 mm	For max. wall thickness	2,5 mm
Length	75 mm	For wall thickness	1,5 - 2,5 mm
		Suitable for grommets	2 x QT small

KEL-QTA 10|2-DP 6 B




Part No.	43659	Width	44 mm
EAN	4251269310423	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	14	Cut-out size	65 × 36 mm
Max. cable diam., with connector	15 mm	For min. wall thickness	2,8 mm
Max. cable diam., without connector	5 mm	For max. wall thickness	4 mm
Length	75 mm	For wall thickness	2,8 - 4 mm
		Suitable for grommets	2 x QT small

KEL-QTA 10|1-DP 18 A




Part No.	43655	Width	44 mm
EAN	4251269310393	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	22	Cut-out size	65 × 36 mm
Max. cable diam., with connector	15 mm	For min. wall thickness	1,5 mm
Max. cable diam., without connector	5 mm	For max. wall thickness	2,5 mm
Length	75 mm	For wall thickness	1,5 - 2,5 mm
		Suitable for grommets	1 x QT small

KEL-QTA 10|1-DP 18 B




Part No.	43658	Width	44 mm
EAN	4251269310416	Height	12 mm
Package quantity	10	Mounting height	5 mm
For max. no. of cables	22	Cut-out size	65 × 36 mm
Max. cable diam., with connector	15 mm	For min. wall thickness	2,8 mm
Max. cable diam., without connector	5 mm	For max. wall thickness	4 mm
Length	75 mm	For wall thickness	2,8 - 4 mm
		Suitable for grommets	1 x QT small


KEL-QTA-B4 A

Part No.	43660
EAN	4251269310430
Package quantity	10
For max. no. of cables	16
Max. cable diam., with connector	15 mm
Length	55 mm
Width	55 mm


Height	11 mm
Mounting height	5 mm
Cut-out size	46 × 46 mm
For min. wall thickness	1,5 mm
For max. wall thickness	2,5 mm
For wall thickness	1,5 - 2,5 mm
Suitable for grommets	4 x QT small

KEL-QTA 32 A


Part No.	43632
EAN	4251269310331
Package quantity	10
For max. no. of cables	4
Max. cable diam., with connector	15 mm
Height	12 mm
Mounting height	5 mm
For min. wall thickness	1,5 mm
For max. wall thickness	2,5 mm
For wall thickness	1,5 - 2,5 mm
Suitable for grommets	1 x QT small

KEL-QTA 32 B

Part No.	43636
EAN	4251269310348
Package quantity	10
For max. no. of cables	4
Max. cable diam., with connector	15 mm
Height	12 mm
Mounting height	5 mm
For min. wall thickness	2,8 mm
For max. wall thickness	4 mm
For wall thickness	2,8 - 4 mm
Suitable for grommets	1 x QT small

KEL-QTA 50 A

Part No.	43622
EAN	4251269310317
Package quantity	10
For max. no. of cables	8
Max. cable diam., with connector	15 mm
Height	12 mm
Mounting height	5 mm
For min. wall thickness	1,5 mm
For max. wall thickness	2,5 mm
For wall thickness	1,5 - 2,5 mm
Suitable for grommets	2 x QT small

KEL-QTA 50 B

Part No.	43626
EAN	4251269310324
Package quantity	10
For max. no. of cables	8
Max. cable diam., with connector	15 mm
Height	12 mm
Mounting height	5 mm
For min. wall thickness	2,8 mm
For max. wall thickness	4 mm
For wall thickness	2,8 - 4 mm
Suitable for grommets	2 x QT small

