KEL | Centrally split cable entry frames

for cables with connectors / IP54 / UL Type 12



IP54	UL TYPE	c 91 °us		RI ^{\$} R	HL3 EN 45545-2
((())) EN 61373	ECOLAB certified	ISO 4892-2A	Made in Germany	RoHS	

The classic KEL is a centrally split cable entry system for routing cables with connectors, providing an IP54 / up to UL Type 12 rating.

The slit <u>KT grommet</u> matching the cable diameter is placed around the cable and inserted into the cable entry frame. The split cable entry frames KEL match exactly the cut-out dimensions of 10-, 16- and 24-pin standard industrial connectors. Either a cut-out of 36 mm or 46 mm in height can be chosen depending on the cables being routed. The size KEL-B matches the cut-out dimensions of 46 × 46 mm measuring instruments.

Based on the frame sizes KEL 16 and KEL 24, there are also extended versions with additional middle frames available. Thus allowing a quick, easy and cost effective routing solution for up to 120 cables or hoses.

For tool-free assembly / disassembly of the cable entry frames the <u>snap mounting</u> <u>frame KEL-SNAP</u> can be used.

A flat rubber gasket is included in the shipment.

This product is available in different versions: With steel screws or stainless steel screws. It is also possible to integrate threaded bushings. Please ask us about your desired variant.

The version with threaded bushings enables the cable entry frame to be screwed onto the housing from the inside out. This protects against vandalism and tampering with the housing from the outside.

Specifications

IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, silicone free, anti- corrosive (V2A versions), halogen free, UV-resistant
Mounting options	Screw type mounting,Snap-in with KEL-SNAP
Mounting height	17 mm

Advantages & benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Strain relief according to EN 62444
- High stability, vibration resistant
- Space-saving shape
- Greatly increased cable density when using double or quadruple grommets

Product types & sizes

KEL	24	10

0			0
0			0

Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material

Min. cable diam., with connector Suitable for grommets

17 mm 17 mm 112 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated

10 x KT small

KEL 24|10 V2A

	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42241.200 4251269308284 10 40 17 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Stainless steel (V2A) 10 x KT small
KEL 24 7	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42247 4251269308314 10 25 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 6 x KT small 1 x KT large
KEL 24 7 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42247.200 4251269308321 10 25 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Stainless steel (V2A) 6 x KT small 1 x KT large
KEL 24 5	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42248 4251269308338 10 20 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 5 x KT small
KEL 24 5 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42248.200 4251269308345 10 20 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Stainless steel (V2A) 5 x KT small



Part No.

EAN

42244

4251269308291

	Package quantity For max. no. of cables Max. cable diameter Length Width	10 10 35 mm 147 mm 58 mm	Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 112 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 2 x KT small 2 x KT large
KEL 24 4 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42244.200 4251269308307 10 10 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Stainless steel (V2A) 2 x KT small 2 x KT large
KEL 24 15-E	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42209 4251269308017 1 60 17 mm 147 mm 83 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 66 mm 4 5,8 mm Mild steel, galvanically zinc plated 15 x KT small
KEL 24 15-E V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42209.200 4251269308024 1 60 17 mm 147 mm 83 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 66 mm 4 5,8 mm Stainless steel (V2A) 15 x KT small
KEL 24 12-E	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42208 4251269307997 1 45 35 mm 147 mm 83 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 66 mm 4 5,8 mm Mild steel, galvanically zinc plated 11 x KT small 1 x KT large

Height

Mounting height

17 mm

17 mm

KEL 24 12-E V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42208.200 4251269308000 1 45 35 mm 147 mm 83 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 66 mm 4 5,8 mm Stainless steel (V2A) 11 x KT small 1 x KT large
KEL 24 10-E	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	49056 4251269312212 1 39 35 mm 147 mm 83 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 66 mm 4 5,8 mm Mild steel, galvanically zinc plated 10 x KT small
KEL 24 10-E V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	49056.200 4251269312229 1 40 35 mm 147 mm 83 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 66 mm 4 5,8 mm Stainless steel (V2A) 10 x KT small
KEL 24 9-E	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42207 4251269307973 1 30 35 mm 147 mm 83 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 66 mm 4 5,8 mm Mild steel, galvanically zinc plated 7 x KT small 2 x KT large
KEL 24 9-E V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42207.200 4251269307980 1 30 35 mm 147 mm 83 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 66 mm 4 5,8 mm Stainless steel (V2A) 7 x KT small 2 x KT large

KEL 24|20-MT

0			0
0			0
0			0

Part No.	42232	Height	17 mm
EAN	4251269308215	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	80	No. of screw holes	6
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc
Width	102 mm		plated

Suitable for grommets

Min. cable diam., with connector

KEL 24|20-MT V2A

0				0
0				0
0				0

Part No.	42232.200
EAN	425126930
Package quantity	1
For max. no. of cables	80
Max. cable diameter	17 mm
Length	147 mm
Width	102 mm

Height 4251269308222 Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets

17 mm 17 mm 112 × 82 mm 6 5,8 mm Stainless steel (V2A) Min. cable diam., with connector 20 x KT small

20 x KT small

KEL 24|17-MT

0				0
0				0
Ľ				Č
0				0

Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

42224
4251269308130
1
65
35 mm
147 mm
102 mm

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets

17 mm 17 mm 112 × 82 mm 6 5,8 mm Mild steel, galvanically zinc plated

16 x KT small 1 x KT large

KEL 24|17-MT V2A



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

42224.200 4251269308147 1 65 35 mm 147 mm 102 mm

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets

17 mm 17 mm 112 × 82 mm 6 5,8 mm Stainless steel (V2A)

16 x KT small 1 x KT large

KEL 24|14-MT

_			
0			 0
0			 0
0			 0

Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material

Min. cable diam., with connector Suitable for grommets

17 mm 17 mm 112 × 82 mm 6 5,8 mm Mild steel, galvanically zinc plated

12 x KT small 2 x KT large

KEL 24 14-MT V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42225.200 4251269308161 1 48 35 mm 147 mm 102 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 82 mm 6 5,8 mm Stainless steel (V2A) 12 x KT small 2 x KT large
KEL 24 11-MT	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42222 4251269308093 1 35 35 mm 147 mm 102 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 82 mm 6 5,8 mm Mild steel, galvanically zinc plated 8 x KT small 3 x KT large
KEL 24 11-MT V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42222.200 4251269308109 1 35 35 mm 147 mm 102 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 82 mm 6 5,8 mm Stainless steel (V2A) 8 x KT small 3 x KT large
KEL 24 8-MT	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42221 4251269308079 1 20 35 mm 147 mm 102 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 82 mm 6 5,8 mm Mild steel, galvanically zinc plated 4 x KT small 4 x KT large
KEL 24 8-MT V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42221.200 4251269308086 1 20 35 mm 147 mm 102 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 112 × 82 mm 6 5,8 mm Stainless steel (V2A) 4 x KT small 4 x KT large

KEL 24|30-2MT



Part No.	42234	Height	17 mm
EAN	4251269308253	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	120	No. of screw holes	8
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc
Width	146 mm		plated
		Min. cable diam., with connector	

30 x KT small

17 mm

17 mm

5,8 mm

8

112 × 126 mm

30 x KT small

Stainless steel (V2A)

KEL 24|30-2MT V2A

	0
°	0

KEL 24|27-2MT

0					0
0			ļ		0
۳.					Ľ
0					0
10			Ĩ		i U
			Η		
0					lo
	 	<u> </u>		 	

Part No. EAN Package quantity For max. no. of cables Max. cable diameter

Part No.

Length

Width

Package quantity

For max. no. of cables

Max. cable diameter

EAN

42234.200

1

120

17 mm

147 mm

146 mm

4251269308260

Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets

Suitable for grommets

Height

Height

Mounting height

No. of screw holes

Screw material

Diam. of screw holes

Suitable for grommets

Min. cable diam., with connector

Cut-out size

17 mm 17 mm 112 × 126 mm 8 5,8 mm Mild steel, galvanically zinc plated

26 x KT small 1 x KT large

KEL 24|27-2MT V2A

0					0
-			H		
					0
0					
0	-				0
0					0

Part No.

Length Width

Part NO.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42233.200 4251269308246 1 105 35 mm 147 mm 146 mm Height17Mounting height17Cut-out size11No. of screw holes8Diam. of screw holes5,8Screw material54Min. cable diam., with connector5Suitable for grommets26

17 mm 17 mm 112 × 126 mm 8 5,8 mm Stainless steel (V2A)

26 x KT small 1 x KT large

KEL 24|24-2MT

0				0
0				0
0				0
Ŭ				
0]		0

Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

42227
4251269308192
1
90
35 mm
147 mm
146 mm

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material

Min. cable diam., with connector Suitable for grommets

17 mm 17 mm 112 × 126 mm 8 5,8 mm Mild steel, galvanically zinc plated

22 x KT small 2 x KT large

KEL	24	24-2MT	V2A

0			0
0			0
0			0
0		1	0

Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

42227.200 4251269308208 1 90 35 mm 147 mm 146 mm

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets

17 mm 17 mm 112 × 126 mm 8 5,8 mm Stainless steel (V2A) 22 x KT small 2 x KT large

	EAN Package quantity For max. no. of cables Max. cable diameter	4251269308178 1 75 35 mm	Mounting height Cut-out size No. of screw holes Diam. of screw holes	17 mm 112 × 126 mm 8 5,8 mm
• • • Length • • • • • • •	•	147 mm 146 mm	Screw material Min. cable diam., with connector Suitable for grommets	18 x KT small
				3 x KT large
		42226.200	Height	17 mm
EL 24 21-2MT V2A	Part No.	42220.200	neight	1 / IIIII
EL 24 21-2MT V2A	Part No. EAN	42226.200 4251269308185	Mounting height	17 mm

EAN	4251269308185	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	75	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	18 x KT small
			3 x KT large
	For max. no. of cables Max. cable diameter Length	For max. no. of cables75Max. cable diameter35 mmLength147 mm	For max. no. of cables75No. of screw holesMax. cable diameter35 mmDiam. of screw holesLength147 mmScrew materialWidth146 mmMin. cable diam., with connector

KEL 24 12-2MT	Part No.	42223
	EAN	4251269308116
	Package quantity	1
o <u> </u>	For max. no. of cables	30
	Max. cable diameter	35 mm
o o	Length	147 mm
	Width	146 mm

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector

Suitable for grommets

17 mm 17 mm 112 × 126 mm 8 5,8 mm Mild steel, galvanically zinc plated 6 x KT small

6 x KT large

KEL 24|12-2MT V2A

0		0
0		0
0		0
0		0

Part No.

- EAN Package quantity For max. no. of cables Max. cable diameter Length Width
- 42223.200 4251269308123 1 30 35 mm 147 mm 146 mm
- Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets
- 17 mm 17 mm 112 × 126 mm 8 5,8 mm Stainless steel (V2A) 6 x KT small

6 x KT large

KEL 16|8

\square			
0			0
<u> </u>			_
0			
10			10

	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42168 4251269307911 10 32 17 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 8 x KT small
KEL 16 8 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42168.200 4251269307928 10 30 17 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Stainless steel (V2A) 8 x KT small
KEL 16 5	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42165 4251269307898 10 17 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 4 x KT small 1 x KT large
KEL 16 5 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42165.200 4251269307904 10 17 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Stainless steel (V2A) 4 x KT small 1 x KT large
KEL 16 4	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42164 4251269307874 10 16 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 4 x KT small

KEL 16|4 V2A

	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42164.200 4251269307881 10 16 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Stainless steel (V2A) 4 x KT small
KEL 16 2	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42162 4251269307850 10 2 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 2 x KT large
KEL 16 2 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42162.200 4251269307867 10 2 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Stainless steel (V2A) 2 x KT large
KEL 16 12-E	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42141 4251269307713 1 48 17 mm 120 mm 84 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 66 mm 4 5,8 mm Mild steel, galvanically zinc plated 12 x KT small
KEL 16 12-E V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42141.200 4251269307720 1 48 17 mm 120 mm 84 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 66 mm 4 5,8 mm Stainless steel (V2A) 12 × KT small

KEL 16|6-E



Part No.

42140

	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42140 4251269307690 1 18 35 mm 120 mm 84 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 66 mm 4 5,8 mm Mild steel, galvanically zinc plated 4 x KT small 2 x KT large
KEL 16 6-E V2A	Part No.	42140.200	Height	17 mm
	EAN	4251269307706	Mounting height	17 mm
	Package quantity	1	Cut-out size	86 × 66 mm
	For max. no. of cables	18	No. of screw holes	4
0 0	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	120 mm	Screw material	Stainless steel (V2A)
	Width	84 mm	Min. cable diam., with connector	
			Suitable for grommets	4 x KT small
				2 x KT large
KEL 16 16-MT	Part No.	42145	Height	17 mm
	EAN	4251269307775	Mounting height	17 mm
0 0	Package quantity	1	Cut-out size	86 × 82 mm
	For max. no. of cables	64	No. of screw holes	6
	Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
	Length	120 mm	Screw material	Mild steel, galvanically zinc
	Width	102 mm		plated
			Min. cable diam., with connector	
			Suitable for grommets	16 x KT small
KEI 16116 MT 1/24				
KEL 16 16-MT V2A	Part No.	42145.200	Height	17 mm
0 0	EAN	4251269307782	Mounting height	17 mm
	Package quantity	1	Cut-out size	86 × 82 mm
0 0	For max. no. of cables	61 17 mm	No. of screw holes	6 5 8 mm
	Max. cable diameter	17 mm 120 mm	Diam. of screw holes Screw material	5,8 mm Stainlags steel ()(2A)
o o	Length Width	120 mm 102 mm	Min. cable diam., with connector	Stainless steel (V2A)
	WIGUI	102 11111	min. cable ulam, with connector	

Height

16 x KT small

17 mm

KEL 16|10-MT



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material

Min. cable diam., with connector Suitable for grommets

Suitable for grommets

17 mm 17 mm 86 × 82 mm 6 5,8 mm Mild steel, galvanically zinc plated

8 x KT small 2 x KT large

KEL 16 10-MT V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42144.200 4251269307768 1 34 35 mm 120 mm 102 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 82 mm 6 5,8 mm Stainless steel (V2A) 8 x KT small 2 x KT large
KEL 16 4-MT	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42143 4251269307737 1 4 35 mm 120 mm 102 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 82 mm 6 5,8 mm Mild steel, galvanically zinc plated 4 x KT large
KEL 16 4-MT V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42143.200 4251269307744 1 4 35 mm 120 mm 102 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 82 mm 6 5,8 mm Stainless steel (V2A) 4 x KT large
KEL 16 24-2MT	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42149 4251269307836 1 96 17 mm 120 mm 146 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 126 mm 8 5,8 mm Mild steel, galvanically zinc plated 24 x KT small
KEL 16 24-2MT V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42149.200 4251269307843 1 96 17 mm 120 mm 146 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 86 × 126 mm 8 5,8 mm Stainless steel (V2A) 24 x KT small
KEL 16 12-2MT	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length	42148 4251269307812 1 36 35 mm 120 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material	17 mm 17 mm 86 × 126 mm 8 5,8 mm Mild steel, galvanically zinc

Length

Width

0

0

0

0

120 mm

146 mm

Min. cable diam., with connector Suitable for grommets

Screw material

5,8 mm Mild steel, galvanically zinc plated

8 x KT small

4 x KT large

KEL 16 12-2MT V2A	Part No.	42148.200	Height	17 mm
	EAN	4251269307829	Mounting height	17 mm
	Package quantity	1	Cut-out size	86 × 126 mm
	For max. no. of cables	36	No. of screw holes	8
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	120 mm	Screw material	Stainless steel (V2A)
0 0	Width	146 mm	Min. cable diam., with connector	
			Suitable for grommets	8 x KT small
oo				2 x KT large
KEL 16 6-2MT	Part No.	42147	Height	17 mm
- [] -	EAN	4251269307799	Mounting height	17 mm
°	Package quantity	1	Cut-out size	86 × 126 mm
	For max. no. of cables	6	No. of screw holes	8
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	120 mm	Screw material	Mild steel, galvanically zinc
。。	Width	146 mm		plated
			Min. cable diam., with connector	
0 0			Suitable for grommets	6 x KT large
KEL 16 6-2MT V2A	Part No.	42147.200	Height	17 mm
	EAN	4251269307805	Mounting height	17 mm
	Package quantity	1	Cut-out size	86 × 126 mm
	For max. no. of cables	6	No. of screw holes	8
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	120 mm	Screw material	Stainless steel (V2A)
	Width	146 mm	Min. cable diam., with connector	Stanness steer (VZA)
Ŭ	Width	146 mm	Suitable for grommets	6 x KT large
00			Suitable for gronninets	o x Ki laige
KEL 10 6	Part No.	42216	Height	17 mm
	EAN	4251269308055	Mounting height	17 mm
	Package quantity	10	Cut-out size	65 × 36 mm
	For max. no. of cables	24	No. of screw holes	4
	Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
)	Length	98 mm	Screw material	Mild steel, galvanically zinc
	Width	58 mm		plated
			Min. cable diam., with connector	
			Suitable for grommets	6 x KT small
				6 x KT small
EL 10 6 V2A	Part No.	42216.200	Height	17 mm
	EAN	4251269308062	Mounting height	17 mm
	Package quantity	10	Cut-out size	65 × 36 mm
0 0 0		24	No. of screw holes	4
0 0	For max, no of cables			•
	For max. no. of cables		Diam of screw holes	5.8 mm
	Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm Stainless steel (V/2A)
	Max. cable diameter Length	17 mm 98 mm	Screw material	5,8 mm Stainless steel (V2A)
	Max. cable diameter	17 mm		

KEL 10|3



	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42212 4251269308031 10 9 35 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 65 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 2 x KT small 1 x KT large
KEL 10 3 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42212.200 4251269308048 10 9 35 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 65 × 36 mm 4 5,8 mm Stainless steel (V2A) 2 x KT small 1 x KT large
KEL-B4	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42204 4251269307935 10 16 17 mm 72 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 46 × 46 mm 4 5,8 mm Mild steel, galvanically zinc plated 4 x KT small
KEL-B4 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42204.200 4251269307942 10 16 17 mm 72 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets	17 mm 17 mm 46 × 46 mm 4 5,8 mm Stainless steel (V2A) 4 x KT small
KEL-B1	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42206 4251269307959 10 1 35 mm 72 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector	17 mm 17 mm 46 × 46 mm 4 5,8 mm Mild steel, galvanically zinc plated

1 x KT large

Suitable for grommets

KEL-B1 V2A



Part No.

EAN Package quantity For max. no. of cables Max. cable diameter Length Width 42206.200 4251269307966 10 1 35 mm 72 mm 58 mm Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Min. cable diam., with connector Suitable for grommets

17 mm 17 mm 46 × 46 mm 4 5,8 mm Stainless steel (V2A)

1 x KT large

