

KT-DPF | Multi-range cable grommets, grey

in pyramid shape, for cable diameters 3-26 mm / IP54 / UL Type 12



The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

It is recommended that additional strain relief be provided for the cables using a cable tie.

Cutting of KT-DPF grommets: Cable diameter less 20%.



Specifications


IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free

Advantages & benefits

- Large clamping range of 3 to 26 mm with only 3 grommets
- Ideal for wiring non pre-terminated cables locally
- Easy storage

Product types & sizes


KT-DPF-A gy



Part No.	41260
EAN	4251269306730
Package quantity	10
For max. no. of cables	1
Colour	grey (similar RAL 7035)
Length	21 mm
Width	21 mm


Height	50 mm
Mounting height	33 mm
For cable type	Round cable
Clamping range	3 - 12 mm
Clamping range	1 x 3 - 12 mm

KT-DPF-B gy



Part No.	41261
EAN	4251269306747
Package quantity	10
For max. no. of cables	1
Colour	grey (similar RAL 7035)
Length	41,5 mm
Width	42 mm

Height	59 mm
Mounting height	42 mm
For cable type	Round cable
Clamping range	4 - 18 mm
Clamping range	1 x 4 - 18 mm



Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41262
4251269306754
10
1
grey (similar RAL 7035)
41,5 mm
42 mm

Height
Mounting height
For cable type
Clamping range
Clamping range

59 mm
42 mm
Round cable
14 - 26 mm
1 x 14 - 26 mm

icotek[®]
smart cable management