

CONFIX™ WST split cable protection conduits

for cables with connectors



The CONFIX™ WST is a two piece corrugated conduit. Perfect for routing cables with or without connectors in rough environments.

In conjunction with e.g. [KVT-W90](#), a high degree of flexibility is achieved. Numerous conduit sizes can be used thanks to the wide variety of [split grommets](#) offered.

The length of the CONFIX™ WST split corrugated conduit can be customized to your application.

Defining your individual length:

Order numbers (ex.):

Length = 1.500 mm --> Order No. 31200.01500

All conduits are available by the metre (0.5 m steps).

Specifications

Material	Polypropylene
Operating temperature	-30 C° to 105 C°
Properties	UV-resistant

Advantages & benefits

 Retrofits, repairs and maintenance can be done much more easily and quickly

Product types & sizes

CONFIX™ WST NW 10



Part No.	31200.xxxxx
EAN	
Package quantity	1
Nominal size	NW 10
External diameter	13,6 mm
Internal diameter	8,7 mm
Bending radius (static)	25 mm

CONFiX™ WST NW 14



Part No.	31210.xxxxx	Compatible	31410,
EAN		with CONFiX™	31411
Package	1	FWS	
quantity			
Nominal size	NW 14		
External	18,5 mm		
diameter			
Internal	12,5 mm		
diameter			
Bending radius	35 mm		
(static)			

CONFiX™ WST NW 16



Part No.	31215.xxxxx	Compatible	31413,
EAN		with CONFiX™	31414
Package	1	FWS	
quantity			
Nominal size	NW 16		
External	21,5 mm		
diameter			
Internal	16 mm		
diameter			
Bending radius	40 mm		
(static)			

CONFiX™ WST NW 20

Part No.	31220.xxxxx
EAN	
Package quantity	1
Nominal size	NW 20
External diameter	25,5 mm
Internal diameter	19,5 mm
Bending radius (static)	45 mm



CONFiX™ WST NW 23

Part No.	31230.xxxxx	Compatible with CONFiX™ FWS	31416, 31417
EAN			
Package quantity	1		
Nominal size	NW 23		
External diameter	31 mm		
Internal diameter	24,2 mm		
Bending radius (static)	50 mm		



CONFiX™ WST NW 29



Part No.	31235.xxxxx	Compatible	31419,
EAN		with CONFiX™	31420
Package	1	FWS	
quantity			
Nominal size	NW 29		
External	35,5 mm		
diameter			
Internal	27,3 mm		
diameter			
Bending radius	90 mm		
(static)			

CONFiX™ WST NW 37



Part No.	31240.xxxxx	Compatible	31422,
EAN		with CONFiX™	31423
Package	1	FWS	
quantity			
Nominal size	NW 37		
External	41,4 mm		
diameter			
Internal	31 mm		
diameter			
Bending radius	110 mm		
(static)			

CONFIX™ WST NW 45

Part No.	31250.xxxxx	Compatible	31425,
EAN		with CONFIX™	31426
Package	1	FWS	
quantity			
Nominal size	NW 45		
External	54 mm		
diameter			
Internal	42,7 mm		
diameter			
Bending radius	130 mm		
(static)			



CONFIX™ WST NW 70

Part No.	31260.xxxxx		
EAN			
Package	1		
quantity			
Nominal size	NW 70		
External	79,8 mm		
diameter			
Internal	66,5 mm		
diameter			
Bending radius	190 mm		
(static)			



