EMC-KVT-DS | Split EMC cable gland

for shielding cables with connectors, thread size M32/M63 / IP55



The split cable gland EMC-KVT-DS is based on the standard icotek KVT product. However, the EMC-KVT-DS has been metallised (galvanise coated) to create a conductive surface.

The first cable grommet (KT) is used for strain relief and cable sealing on the cable jacket. The second grommet (EMC-KT) contacts the cable shield at a full 360 degrees.

The conductive flat gasket included in the scope of delivery makes contact between the cable gland and the conductive housing wall. The EMC-KVT-DS can thus be fixed using a plastic lock nut. Alternatively, an additional contact to the metal wall can be made using a special EMC lock nut.

Specifications

IP rating (EN 60529) Material	IP54, IP55 Polycarbonate, highly conductive coating Locknut: Brass, nickel-plated Locknut: Plastic	 Both conducted and field-bound disturbances can be reliably diverted Scratch-resistant surface Contacting the cable shield over 360° EMC grommets made entirely from conductive elastomer Very good dissipation values
Flame class	UL94-HB	Very good shielding effect with regard to EMC tightness
Operating temperature	-40 C° to 90 C°	
Mounting options	Fasten with locknut	

Product types & sizes

EMC-KVT-DS 32 with plastic locknut	Part No. EAN Package quantity For max. no. of cables Max. cable diameter	99431 4251269321962 5 1 17 mm 22 mm	Cut-out size, round Thread Thread length Suitable for grommets	32,3 mm M32 × 1,5 14 mm 1 x KT small 1 x EMC-KT small
	Mounting height	23 mm		
	Cut-out size, metric	M32		

EMC	-KVT-DS	32	with	
EMC	locknut			



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Mounting height Cut-out size, metric

Cut-out size, round Thread Thread length Suitable for grommets

Advantages & benefits

32,3 mm M32 × 1,5 14 mm 1 x KT small 1 x EMC-KT small

	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Mounting height Cut-out size, metric	99434 4251269322587 1 1 35 mm 23 mm M63	Cut-out size, round Thread Thread length Screw material Suitable for grommets	63,4 mm M63 × 1,5 14 mm Stainless steel (V2A) 1 x KT large 1 x EMC-KT large
EMC-KVT-DS 63 1 with EMC locknut	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Mounting height Cut-out size, metric	99435 4251269322594 1 1 35 mm 23 mm M63	Cut-out size, round Thread Thread length Screw material Suitable for grommets	63,4 mm M63 × 1,5 14 mm Stainless steel (V2A) 1 x KT large 1 x EMC-KT large
EMC-KVT-DS 63 4 with EMC locknut	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Mounting height Cut-out size, metric	99437 4251269322617 1 4 17 mm 23 mm M63	Cut-out size, round Thread Thread length Screw material Suitable for grommets	63,4 mm M63 × 1,5 14 mm Stainless steel (V2A) 4 x KT small 4 x EMC-KT small
EMC-KVT-DS 63 4 with plastic locknut	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Mounting height Cut-out size, metric	99436 4251269322600 1 4 17 mm 23 mm M63	Cut-out size, round Thread Thread length Screw material Suitable for grommets	63,4 mm M63 × 1,5 14 mm Stainless steel (V2A) 4 x KT small 4 x EMC-KT small

EMC gasket 32



Part No.	99555
EAN	4251269322
	631
Package	5
quantity	
Height	2,5 mm
External	38 mm
diameter	



56
1269322
;
mm
mm

EMC-GM 32

Part No.	99557
EAN	4251269321
	979
Package	5
quantity	
Height	4,5 mm



EMC-GM 63



Part No. EAN	99558 4251269322 624
Package	1
quantity Height	7 mm

