

KEL-DPZ CR multi-membrane cable entry plates

for the use in cleanrooms / up to IP66 / UL Type 12



IP54

UL TYPE 12

EN 61373

RoHS compliant

IP55

CULUS

ECOLAB certified

REACH COMPLIANCE

IP64

IP65

ISO 4892-2A

Made in Germany

IP65

RIFA

EN ISO 14644

IP66

HL3 EN 45545-2

PNEUMATICS



KEL-DPZ CR cable entry plates are designed to route and seal a large number cables without connectors, hoses or fibre optics (from 1.5 mm to 22 mm in diameter) in limited space.

The KEL-DPZ CR products are a cost and time saving alternative to traditional cable glands.

The assembly of the KEL-DPZ CR with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ CR provides strain relief and protection up to IP66 / UL type 12.

The KEL-DPZ CR matches exactly the cut-out dimensions of 6-, 16- and 24-pin standard industrial connectors. The size KEL-DPZ-B CR fits on cut-outs 46 × 46 mm. The very compact size KEL-DPZ-E CR is designed for routing cables in very small space. Through a cut-out of only 18 × 112 mm, up to 21 cables can be easily routed and sealed.

Especially for Rittal KL / KX terminal boxes the size KEL-DPZ-KX/KL CR (IP65) was created. It was designed for routing up to 72 cables through the pre-cut standard cut-out. The self-tapping screws required for assembly are included in the scope of delivery.

The products with article ending .600 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1. The materials used for these products have been tested and certified for outgassing according to VOC/SVOC (ISO 14644-8; ISO 16000-6,-9,-11,-25, VDI 2083 sheet 17).

The products with the article ending .601 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1.

Specifications


IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66
UL Type (UL 50E)	UL Type 12
Material	Elastomer Base frame: Polyamide Base frame: Stainless steel (V2A)
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free
Mounting options	Screw type mounting

Product types & sizes

Advantages & benefits


- Fast mounting
- High cable density
- Certified protection up to IP66 (acc. to EN 60529)
- Automatic sealing and strain relief for the cable
- Hygienic design - free of dirt-collecting recesses
- Space-saving shape

KEL-DPZ 24|14 CR gy




Part No.	43700.601	Width	58 mm
EAN	4251269327315	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	14	Cut-out size	112 × 36 mm
Max. cable diameter	22 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	10 x 3.2 - 6.5 mm 4 x 16 - 22 mm

KEL-DPZ 24|14 CR (S)VOC gy



Part No.	43700.600	Width	58 mm
EAN	4251269327148	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	14	Cut-out size	112 × 36 mm
Max. cable diameter	22 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	10 x 3.2 - 6.5 mm 4 x 16 - 22 mm

KEL-DPZ 24|14 CR bk




Part No.	50700.601	Width	58 mm
EAN	4251269327407	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	14	Cut-out size	112 × 36 mm
Max. cable diameter	22 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	10 x 3.2 - 6.5 mm 4 x 16 - 22 mm

KEL-DPZ 24|14 CR (S)VOC bk




Part No.	50700.600	Width	58 mm
EAN	4251269327223	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	14	Cut-out size	112 × 36 mm
Max. cable diameter	22 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	10 x 3.2 - 6.5 mm 4 x 16 - 22 mm

KEL-DPZ 24|15 CR gy





Part No.	43720.601	Width	58 mm
EAN	4251269327360	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	15	Cut-out size	112 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	15 x 7.5 - 12 mm


KEL-DPZ 24|15 CR (S)VOC gy




Part No.	43720.600	Width	58 mm
EAN	4251269327186	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	15	Cut-out size	112 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	15 x 7.5 - 12 mm

KEL-DPZ 24 15 CR (S)VOC bk 	Part No.	50720.600	Width	58 mm
	EAN	4251269327278	Height	14 mm
	Package quantity	5	Mounting height	14 mm
	For max. no. of cables	15	Cut-out size	112 × 36 mm
	Max. cable diameter	12 mm	No. of screw holes	4
	Colour	black	Diam. of screw holes	5,9 mm
	Length	147 mm	(S)VOC tested	ja
			Clamping range	15 x 7.5 - 12 mm


KEL-DPZ 24 15 CR bk 	Part No.	50720.601	Width	58 mm
	EAN	4251269327452	Height	14 mm
	Package quantity	5	Mounting height	14 mm
	For max. no. of cables	15	Cut-out size	112 × 36 mm
	Max. cable diameter	12 mm	No. of screw holes	4
	Colour	black	Diam. of screw holes	5,9 mm
	Length	147 mm	(S)VOC tested	nein
			Clamping range	15 x 7.5 - 12 mm

KEL-DPZ 24 16 CR gy 	Part No.	43725.601	Width	58 mm
	EAN	4251269327377	Height	14 mm
	Package quantity	5	Mounting height	14 mm
	For max. no. of cables	16	Cut-out size	112 × 36 mm
	Max. cable diameter	22 mm	No. of screw holes	4
	Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
	Length	147 mm	(S)VOC tested	nein
			Clamping range	8 x 3.2 - 6.5 mm 4 x 5 - 9.7 mm 2 x 9 - 16.2 mm 2 x 16 - 22 mm

KEL-DPZ 24 16 CR (S)VOC gy 	Part No.	43725.600	Width	58 mm
	EAN	4251269327193	Height	14 mm
	Package quantity	5	Mounting height	14 mm
	For max. no. of cables	16	Cut-out size	112 × 36 mm
	Max. cable diameter	22 mm	No. of screw holes	4
	Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
	Length	147 mm	(S)VOC tested	ja
			Clamping range	8 x 3.2 - 6.5 mm 4 x 5 - 9.7 mm 2 x 9 - 16.2 mm 2 x 16 - 22 mm


KEL-DPZ 24 16 CR (S)VOC bk 	Part No.	50725.600	Width	58 mm
	EAN	4251269327285	Height	14 mm
	Package quantity	5	Mounting height	14 mm
	For max. no. of cables	16	Cut-out size	112 × 36 mm
	Max. cable diameter	22 mm	No. of screw holes	4
	Colour	black	Diam. of screw holes	5,9 mm
	Length	147 mm	(S)VOC tested	ja
			Clamping range	8 x 3.2 - 6.5 mm 4 x 5 - 9.7 mm 2 x 9 - 16.2 mm 2 x 16 - 22 mm

KEL-DPZ 24|16 CR bk




Part No.	50725.601	Width	58 mm
EAN	4251269327469	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	16	Cut-out size	112 × 36 mm
Max. cable diameter	22 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	8 x 3.2 - 6.5 mm
			4 x 5 - 9.7 mm
			2 x 9 - 16.2 mm
			2 x 16 - 22 mm

KEL-DPZ 24|17 CR
(S)VOC gy




Part No.	43705.600	Width	58 mm
EAN	4251269325458	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	17	Cut-out size	112 × 36 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	6 x 3.2 - 6.5 mm
			6 x 5 - 10.2 mm
			5 x 9 - 16.2 mm

KEL-DPZ 24|17 CR gy




Part No.	43705.601	Width	58 mm
EAN	4251269327322	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	17	Cut-out size	112 × 36 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	6 x 3.2 - 6.5 mm
			6 x 5 - 10.2 mm
			5 x 9 - 16.2 mm

KEL-DPZ 24|17 CR bk




Part No.	50705.601	Width	58 mm
EAN	4251269327414	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	17	Cut-out size	112 × 36 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	6 x 3.2 - 6.5 mm
			6 x 5 - 10.2 mm
			5 x 9 - 16.2 mm

KEL-DPZ 24|17 CR
(S)VOC bk




Part No.	50705.600	Width	58 mm
EAN	4251269327230	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	17	Cut-out size	112 × 36 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	6 x 3.2 - 6.5 mm
			6 x 5 - 10.2 mm
			5 x 9 - 16.2 mm




Part No. **43710.601**
EAN **4251269327339**
Package quantity **5**
For max. no. of cables **25**
Max. cable diameter **12 mm**
Colour **grey (similar RAL 7035)**
Length **147 mm**

Width **58 mm**
Height **14 mm**
Mounting height **14 mm**
Cut-out size **112 x 36 mm**
No. of screw holes **4**
Diam. of screw holes **5,9 mm**
(S)VOC tested **nein**
Clamping range **12 x 3.2 - 6.5 mm**
7 x 4.8 - 9.7 mm
6 x 7.5 - 12 mm




Part No. **43710.600**
EAN **4251269327155**
Package quantity **5**
For max. no. of cables **25**
Max. cable diameter **12 mm**
Colour **grey (similar RAL 7035)**
Length **147 mm**

Width **58 mm**
Height **14 mm**
Mounting height **14 mm**
Cut-out size **112 x 36 mm**
No. of screw holes **4**
Diam. of screw holes **5,9 mm**
(S)VOC tested **ja**
Clamping range **12 x 3.2 - 6.5 mm**
7 x 4.8 - 9.7 mm
6 x 7.5 - 12 mm




Part No. **50710.600**
EAN **4251269327247**
Package quantity **5**
For max. no. of cables **25**
Max. cable diameter **12 mm**
Colour **black**
Length **147 mm**

Width **58 mm**
Height **14 mm**
Mounting height **14 mm**
Cut-out size **112 x 36 mm**
No. of screw holes **4**
Diam. of screw holes **5,9 mm**
(S)VOC tested **ja**
Clamping range **12 x 3.2 - 6.5 mm**
7 x 4.8 - 9.7 mm
6 x 7.5 - 12 mm



Part No. **50710.601**
EAN **4251269327421**
Package quantity **5**
For max. no. of cables **25**
Max. cable diameter **12 mm**
Colour **black**
Length **147 mm**


Width **58 mm**
Height **14 mm**
Mounting height **14 mm**
Cut-out size **112 x 36 mm**
No. of screw holes **4**
Diam. of screw holes **5,9 mm**
(S)VOC tested **nein**
Clamping range **12 x 3.2 - 6.5 mm**
7 x 4.8 - 9.7 mm
6 x 7.5 - 12 mm



Part No. **43711.600**
EAN **4251269327162**
Package quantity **5**
For max. no. of cables **26**
Max. cable diameter **10,2 mm**
Colour **grey (similar RAL 7035)**
Length **147 mm**


Width **58 mm**
Height **14 mm**
Mounting height **14 mm**
Cut-out size **112 x 36 mm**
No. of screw holes **4**
Diam. of screw holes **5,9 mm**
(S)VOC tested **ja**
Clamping range **26 x 5 - 10.2 mm**

KEL-DPZ 24|26 CR gy




Part No.	43711.601	Width	58 mm
EAN	4251269327346	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	26	Cut-out size	112 × 36 mm
Max. cable diameter	10,2 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	26 x 5 - 10.2 mm

KEL-DPZ 24|26 CR bk



Part No.	50711.601	Width	58 mm
EAN	4251269327438	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	26	Cut-out size	112 × 36 mm
Max. cable diameter	10,2 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	26 x 5 - 10.2 mm

KEL-DPZ 24|26 CR (S)VOC bk




Part No.	50711.600	Width	58 mm
EAN	4251269327254	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	26	Cut-out size	112 × 36 mm
Max. cable diameter	10,2 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	26 x 5 - 10.2 mm

KEL-DPZ 24|32 CR gy




Part No.	43730.601	Width	58 mm
EAN	4251269327384	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	32	Cut-out size	112 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	21 x 3.2 - 6.5 mm 8 x 5 - 10.2 mm 3 x 7.5 - 12 mm

KEL-DPZ 24|32 CR (S)VOC gy




Part No.	43730.600	Width	58 mm
EAN	4251269327209	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	32	Cut-out size	112 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	21 x 3.2 - 6.5 mm 8 x 5 - 10.2 mm 3 x 7.5 - 12 mm

KEL-DPZ 24|32 CR bk




Part No.	50730.601	Width	58 mm
EAN	4251269327476	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	32	Cut-out size	112 x 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	21 x 3.2 - 6.5 mm
			8 x 5 - 10.2 mm
			3 x 7.5 - 12 mm

KEL-DPZ 24|32 CR (S)VOC bk




Part No.	50730.600	Width	58 mm
EAN	4251269327292	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	32	Cut-out size	112 x 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	21 x 3.2 - 6.5 mm
			8 x 5 - 10.2 mm
			3 x 7.5 - 12 mm

KEL-DPZ 24|42 CR gy




Part No.	43715.601	Width	58 mm
EAN	4251269327353	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	42	Cut-out size	112 x 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	42 x 3.2 - 6.5 mm

KEL-DPZ 24|42 CR (S)VOC gy



Part No.	43715.600	Width	58 mm
EAN	4251269327179	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	42	Cut-out size	112 x 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	42 x 3.2 - 6.5 mm

KEL-DPZ 24|42 CR bk




Part No.	50715.601	Width	58 mm
EAN	4251269327445	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	42	Cut-out size	112 x 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	42 x 3.2 - 6.5 mm

KEL-DPZ 24|42 CR
(S)VOC bk




Part No.	50715.600	Width	58 mm
EAN	4251269327261	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	42	Cut-out size	112 × 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	42 x 3.2 - 6.5 mm

KEL-DPZ 24|121 CR gy




Part No.	43735.601	Width	58 mm
EAN	4251269327391	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	121	Cut-out size	112 × 36 mm
Max. cable diameter	5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	119 x 1.5 - 2.6 mm 2 x 2.5 - 5 mm

KEL-DPZ 24|121 CR
(S)VOC gy




Part No.	43735.600	Width	58 mm
EAN	4251269327216	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	121	Cut-out size	112 × 36 mm
Max. cable diameter	5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	119 x 1.5 - 2.6 mm 2 x 2.5 - 5 mm

KEL-DPZ 24|121 CR bk




Part No.	50735.601	Width	58 mm
EAN	4251269327483	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	121	Cut-out size	112 × 36 mm
Max. cable diameter	5 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	nein
		Clamping range	119 x 1.5 - 2.6 mm 2 x 2.5 - 5 mm

KEL-DPZ 24|121 CR
(S)VOC bk




Part No.	50735.600	Width	58 mm
EAN	4251269327308	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	121	Cut-out size	112 × 36 mm
Max. cable diameter	5 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,9 mm
Length	147 mm	(S)VOC tested	ja
		Clamping range	119 x 1.5 - 2.6 mm 2 x 2.5 - 5 mm

KEL-DPZ 16|11 CR gy




Part No.	43815.601	Width	58 mm
EAN	4251269327643	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	11	Cut-out size	86 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	nein
		Clamping range	11 x 7.5 - 12 mm

KEL-DPZ 16|11 CR (S)VOC gy




Part No.	43815.600	Width	58 mm
EAN	4251269327544	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	11	Cut-out size	86 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	ja
		Clamping range	11 x 7.5 - 12 mm

KEL-DPZ 16|14 CR gy




Part No.	43816.601	Width	58 mm
EAN	4251269327650	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	14	Cut-out size	86 × 36 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	nein
		Clamping range	5 x 3.2 - 6.5 mm
			5 x 5 - 10.2 mm
			4 x 9 - 16.2 mm

KEL-DPZ 16|14 CR (S)VOC gy




Part No.	43816.600	Width	58 mm
EAN	4251269327551	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	14	Cut-out size	86 × 36 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	ja
		Clamping range	5 x 3.2 - 6.5 mm
			5 x 5 - 10.2 mm
			4 x 9 - 16.2 mm

KEL-DPZ 16|20 CR gy




Part No.	43817.601	Width	58 mm
EAN	4251269327667	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	20	Cut-out size	86 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	nein
		Clamping range	11 x 3.2 - 6.5 mm
			5 x 5 - 10.2 mm
			4 x 7.5 - 12 mm

KEL-DPZ 16|20 CR
(S)VOC gy




Part No.	43817.600	Width	58 mm
EAN	4251269327568	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	20	Cut-out size	86 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	ja
		Clamping range	11 x 3.2 - 6.5 mm
			5 x 5 - 10.2 mm
			4 x 7.5 - 12 mm

KEL-DPZ 16|25 CR gy



Part No.	43818.601	Width	58 mm
EAN	4251269327674	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	25	Cut-out size	86 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	nein
		Clamping range	16 x 3.2 - 6.5 mm
			6 x 5 - 10.2 mm
			3 x 7.5 - 12 mm

KEL-DPZ 16|25 CR
(S)VOC gy




Part No.	43818.600	Width	58 mm
EAN	4251269327575	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	25	Cut-out size	86 × 36 mm
Max. cable diameter	12 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	ja
		Clamping range	16 x 3.2 - 6.5 mm
			6 x 5 - 10.2 mm
			3 x 7.5 - 12 mm

KEL-DPZ 16|34 CR gy




Part No.	43819.601	Width	58 mm
EAN	4251269327681	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	34	Cut-out size	86 × 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	nein
		Clamping range	34 x 3.2 - 6.5 mm

KEL-DPZ 16|34 CR
(S)VOC gy




Part No.	43819.600	Width	58 mm
EAN	4251269327582	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	34	Cut-out size	86 × 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,8 mm
Length	120 mm	(S)VOC tested	ja
		Clamping range	34 x 3.2 - 6.5 mm

KEL-DPZ 6|12 CR gy




Part No.	43809.601	Width	54 mm
EAN	4251269327599	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	12	Cut-out size	52 × 36 mm
Max. cable diameter	8 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	nein
		Clamping range	12 x 4.5 - 8 mm

KEL-DPZ 6|12 CR (S)VOC gy




Part No.	43809.600	Width	54 mm
EAN	4251269327490	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	12	Cut-out size	52 × 36 mm
Max. cable diameter	8 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	ja
		Clamping range	12 x 4.5 - 8 mm

KEL-DPZ 6|18 CR gy




Part No.	43812.601	Width	54 mm
EAN	4251269327612	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	18	Cut-out size	52 × 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	nein
		Clamping range	18 x 3.2 - 6.5 mm

KEL-DPZ 6|18 CR (S)VOC gy




Part No.	43812.600	Width	54 mm
EAN	4251269327513	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	18	Cut-out size	52 × 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	ja
		Clamping range	18 x 3.2 - 6.5 mm

KEL-DPZ 6|18-1 CR gy




Part No.	43811.601	Width	54 mm
EAN	4251269327605	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	18	Cut-out size	52 × 36 mm
Max. cable diameter	8 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	nein
		Clamping range	7 x 4.5 - 8 mm 5 x 3.2 - 6.5 mm 6 x 2.5 - 5 mm

KEL-DPZ 6|18-1 CR
(S)VOC gy




Part No.	43811.600	Width	54 mm
EAN	4251269327506	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	18	Cut-out size	52 × 36 mm
Max. cable diameter	8 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	ja
		Clamping range	7 x 4.5 - 8 mm 5 x 3.2 - 6.5 mm 6 x 2.5 - 5 mm

KEL-DPZ 6|23 CR gy




Part No.	43813.601	Width	54 mm
EAN	4251269327629	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	23	Cut-out size	52 × 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	nein
		Clamping range	10 x 3.2 - 6.5 mm 13 x 2.5 - 5 mm

KEL-DPZ 6|23 CR
(S)VOC gy




Part No.	43813.600	Width	54 mm
EAN	4251269327520	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	23	Cut-out size	52 × 36 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	ja
		Clamping range	10 x 3.2 - 6.5 mm 13 x 2.5 - 5 mm

KEL-DPZ 6|27 CR gy




Part No.	43814.601	Width	54 mm
EAN	4251269327636	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	27	Cut-out size	52 × 36 mm
Max. cable diameter	5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	nein
		Clamping range	27 x 2.5 - 5 mm

KEL-DPZ 6|27 CR
(S)VOC gy




Part No.	43814.600	Width	54 mm
EAN	4251269327537	Height	7,5 mm
Package quantity	5	Mounting height	7,5 mm
For max. no. of cables	27	Cut-out size	52 × 36 mm
Max. cable diameter	5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	4,5
Length	85,5 mm	(S)VOC tested	ja
		Clamping range	27 x 2.5 - 5 mm

KEL-DPZ-B 13 CR gy




Part No.	43794.601	Width	58 mm
EAN	4251269327834	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	13	Cut-out size	46 x 46 mm
Max. cable diameter	22 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	nein
		Clamping range	8 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 1 x 16 - 22 mm

KEL-DPZ-B 13 CR
(S)VOC gy




Part No.	43794.600	Width	58 mm
EAN	4251269327711	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	13	Cut-out size	46 x 46 mm
Max. cable diameter	22 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	ja
		Clamping range	8 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 1 x 16 - 22 mm

KEL-DPZ-B 13 CR bk




Part No.	50794.601	Width	58 mm
EAN	4251269327889	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	13	Cut-out size	46 x 46 mm
Max. cable diameter	22 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	nein
		Clamping range	8 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 1 x 16 - 22 mm

KEL-DPZ-B 13 CR
(S)VOC bk




Part No.	50794.600	Width	58 mm
EAN	4251269327766	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	13	Cut-out size	46 x 46 mm
Max. cable diameter	22 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	ja
		Clamping range	8 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 1 x 16 - 22 mm

KEL-DPZ-B 17 CR gy




Part No.	43796.601	Width	58 mm
EAN	4251269327841	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	17	Cut-out size	46 x 46 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	nein
		Clamping range	10 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 2 x 7.5 - 12 mm 1 x 9 - 16.2 mm

KEL-DPZ-B 17 CR
(S)VOC gy




Part No.	43796.600	Width	58 mm
EAN	4251269327728	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	17	Cut-out size	46 × 46 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	ja
		Clamping range	10 x 3.2 - 6.5 mm
			4 x 5 - 10.2 mm
			2 x 7.5 - 12 mm
			1 x 9 - 16.2 mm

KEL-DPZ-B 17 CR bk




Part No.	50796.601	Width	58 mm
EAN	4251269327896	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	17	Cut-out size	46 × 46 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	nein
		Clamping range	10 x 3.2 - 6.5 mm
			4 x 5 - 10.2 mm
			2 x 7.5 - 12 mm
			1 x 9 - 16.2 mm

KEL-DPZ-B 17 CR
(S)VOC bk




Part No.	50796.600	Width	58 mm
EAN	4251269327773	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	17	Cut-out size	46 × 46 mm
Max. cable diameter	16,2 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	ja
		Clamping range	10 x 3.2 - 6.5 mm
			4 x 5 - 10.2 mm
			2 x 7.5 - 12 mm
			1 x 9 - 16.2 mm

KEL-DPZ-B 25 CR gy




Part No.	43798.601	Width	58 mm
EAN	4251269327858	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	25	Cut-out size	46 × 46 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	nein
		Clamping range	25 x 3.2 - 6.5 mm

KEL-DPZ-B 25 CR
(S)VOC gy




Part No.	43798.600	Width	58 mm
EAN	4251269327735	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	25	Cut-out size	46 × 46 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	ja
		Clamping range	25 x 3.2 - 6.5 mm

KEL-DPZ-B 25 CR bk



Part No.	50798.601	Width	58 mm
EAN	4251269327902	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	25	Cut-out size	46 × 46 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	nein
		Clamping range	25 x 3.2 - 6.5 mm

KEL-DPZ-B 25 CR
(S)VOC bk



Part No.	50798.600	Width	58 mm
EAN	4251269327780	Height	10 mm
Package quantity	5	Mounting height	10 mm
For max. no. of cables	25	Cut-out size	46 × 46 mm
Max. cable diameter	6,5 mm	No. of screw holes	4
Colour	black	Diam. of screw holes	5,7 mm
Length	72,8 mm	(S)VOC tested	ja
		Clamping range	25 x 3.2 - 6.5 mm

KEL-DPZ-E 112|7 CR
gy



Part No.	43780.601	Width	29 mm
EAN	4251269327810	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	7	No. of screw holes	2
Max. cable diameter	12 mm	Diam. of screw holes	5,7 mm
Colour	grey (similar RAL 7035)	(S)VOC tested	nein
Length	147 mm	Clamping range	7 x 7.5 - 12 mm

KEL-DPZ-E 112|7 CR
(S)VOC gy



Part No.	43780.600	Width	29 mm
EAN	4251269327698	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	7	No. of screw holes	2
Max. cable diameter	12 mm	Diam. of screw holes	5,7 mm
Colour	grey (similar RAL 7035)	(S)VOC tested	ja
Length	147 mm	Clamping range	7 x 7.5 - 12 mm

KEL-DPZ-E 112|7 CR
bk



Part No.	50780.601	Width	29 mm
EAN	4251269327865	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	7	No. of screw holes	2
Max. cable diameter	12 mm	Diam. of screw holes	5,7 mm
Colour	black	(S)VOC tested	nein
Length	147 mm	Clamping range	7 x 7.5 - 12 mm

KEL-DPZ-E 112|7 CR
(S)VOC bk



Part No.	50780.600	Width	29 mm
EAN	4251269327742	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	7	No. of screw holes	2
Max. cable diameter	12 mm	Diam. of screw holes	5,7 mm
Colour	black	(S)VOC tested	ja
Length	147 mm	Clamping range	7 x 7.5 - 12 mm

KEL-DPZ-E 112|21 CR
gy



Part No.	43790.601	Width	29 mm
EAN	4251269327827	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	21	No. of screw holes	2
Max. cable diameter	6,5 mm	Diam. of screw holes	5,7 mm
Colour	grey (similar RAL 7035)	(S)VOC tested	nein
Length	147 mm	Clamping range	21 x 3.2 - 6.5 mm

KEL-DPZ-E 112|21 CR
(S)VOC gy



Part No.	43790.600	Width	29 mm
EAN	4251269327704	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	21	No. of screw holes	2
Max. cable diameter	6,5 mm	Diam. of screw holes	5,7 mm
Colour	grey (similar RAL 7035)	(S)VOC tested	ja
Length	147 mm	Clamping range	21 x 3.2 - 6.5 mm

KEL-DPZ-E 112|21 CR
bk




Part No.	50790.601	Width	29 mm
EAN	4251269327872	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	21	No. of screw holes	2
Max. cable diameter	6,5 mm	Diam. of screw holes	5,7 mm
Colour	black	(S)VOC tested	nein
Length	147 mm	Clamping range	21 x 3.2 - 6.5 mm

KEL-DPZ-E 112|21 CR
(S)VOC bk




Part No.	50790.600	Width	29 mm
EAN	4251269327759	Height	14 mm
Package quantity	5	Mounting height	14 mm
For max. no. of cables	21	No. of screw holes	2
Max. cable diameter	6,5 mm	Diam. of screw holes	5,7 mm
Colour	black	(S)VOC tested	ja
Length	147 mm	Clamping range	21 x 3.2 - 6.5 mm

KEL-DPZ-KX/KL 72 CR
gy




Part No.	43675.001.601	Width	90 mm
EAN	4251269327919	Height	4 mm
Package quantity	1	Mounting height	4 mm
For max. no. of cables	72	Cut-out size	192 x 62 mm
Max. cable diameter	22 mm	No. of screw holes	6
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,1 mm
Length	221 mm	(S)VOC tested	nein
		Clamping range	42 x 3.2 - 6.5 mm 21 x 5 - 10.2 mm 6 x 9 - 16.2 mm 3 x 16 - 22 mm

KEL-DPZ-KX/KL 72 CR
(S)VOC gy



Part No.	43675.001.600	Width	90 mm
EAN	4251269327797	Height	4 mm
Package quantity	1	Mounting height	4 mm
For max. no. of cables	72	Cut-out size	192 x 62 mm
Max. cable diameter	22 mm	No. of screw holes	6
Colour	grey (similar RAL 7035)	Diam. of screw holes	5,1 mm
Length	221 mm	(S)VOC tested	ja
		Clamping range	42 x 3.2 - 6.5 mm 21 x 5 - 10.2 mm 6 x 9 - 16.2 mm 3 x 16 - 22 mm


**KEL-DPZ-KX/KL 72 CR
bk**



Part No. **43675.101.601**
EAN **4251269327926**
Package quantity **1**
For max. no. of cables **72**
Max. cable diameter **22 mm**
Colour **black**
Length **221 mm**

Width **90 mm**
Height **4 mm**
Mounting height **4 mm**
Cut-out size **192 x 62 mm**
No. of screw holes **6**
Diam. of screw holes **5,1 mm**
(S)VOC tested **nein**
Clamping range **42 x 3.2 - 6.5 mm**
21 x 5 - 10.2 mm
6 x 9 - 16.2 mm
3 x 16 - 22 mm

**KEL-DPZ-KX/KL 72 CR
(S)VOC bk**



Part No. **43675.101.600**
EAN **4251269327803**
Package quantity **1**
For max. no. of cables **72**
Max. cable diameter **22 mm**
Colour **black**
Length **221 mm**

Width **90 mm**
Height **4 mm**
Mounting height **4 mm**
Cut-out size **192 x 62 mm**
No. of screw holes **6**
Diam. of screw holes **5,1 mm**
(S)VOC tested **ja**
Clamping range **42 x 3.2 - 6.5 mm**
21 x 5 - 10.2 mm
6 x 9 - 16.2 mm
3 x 16 - 22 mm