

KEL-JUMBO | Split cable entry frames

for cables with diameters of up to 65 mm / IP54 / UL Type 12



IP54

ECOLAB certified

UL TYPE 12

UV ISO 4892-2A

CULUS

RoHS compliant

RIIR

REACH COMPLIANCE

HL3 EN 45545-2

Made in Germany

EN 61373

The KEL-JUMBO cable entry system for installation of cables and conduits with a diameter of up to 65 mm, especially suited for supply cables. The innovative grommet design with the flex-membrane provides flexing and adjustment of the position for larger and more rigid cables.

We recommend round cut-outs, which can be made using standard knockout tools. Suggested cut-out: cable diameter +15 - 20%.

A flat rubber gasket is included in the shipment.

Specifications


IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, UV-resistant, silicone free, anti-corrosive (V2A versions), halogen free
Mounting options	Screw type mounting
Mounting height	35 mm


Advantages & benefits

- Installation of cables up to 65 mm in diameter
- It is possible to install rigid cables at angles
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Strain relief according to EN 62444

Product types & sizes

KEL-JUMBO 1 	Part No.	42360	Height	35 mm
	EAN	4251269308550	Mounting height	35 mm
	Package quantity	1	Cut-out size	78 × 80.5 mm
	For max. no. of cables	1	No. of screw holes	4
	Max. cable diameter	65 mm	Diam. of screw holes	7 mm
	Length	110 mm	Screw material	Mild steel, galvanically zinc plated
	Width	116 mm	Suitable for grommets	1 x KTF
KEL-JUMBO 1 V2A 	Part No.	42360.200	Height	35 mm
	EAN	4251269308567	Mounting height	35 mm
	Package quantity	1	Cut-out size	78 × 80.5 mm
	For max. no. of cables	1	No. of screw holes	4
	Max. cable diameter	65 mm	Diam. of screw holes	7 mm
	Length	110 mm	Screw material	Stainless steel (V2A)
	Width	116 mm	Suitable for grommets	1 x KTF

KEL-JUMBO 2 	Part No.	42350	Height	35 mm
	EAN	4251269308536	Mounting height	35 mm
	Package quantity	1	Cut-out size	168 × 80.5 mm
	For max. no. of cables	2	No. of screw holes	4
	Max. cable diameter	65 mm	Diam. of screw holes	7 mm
	Length	200 mm	Screw material	Mild steel, galvanically zinc plated
	Width	116 mm		
			Suitable for grommets	2 x KTF

KEL-JUMBO 2 V2A 	Part No.	42350.200	Height	35 mm
	EAN	4251269308543	Mounting height	35 mm
	Package quantity	1	Cut-out size	168 × 80.5 mm
	For max. no. of cables	2	No. of screw holes	4
	Max. cable diameter	65 mm	Diam. of screw holes	7 mm
	Length	200 mm	Screw material	Stainless steel (V2A)
	Width	116 mm		
			Suitable for grommets	2 x KTF