# KEL-U | KEL-E | Split cable entry frames

for cables with connectors / IP54 / UL Type 12



IP54	UL TYPE	c <b>AL</b> us	RI	EN 45545-2	(( ( ))) EN 61373
ECOLAB certified	ISO 4892-2A	Made in Germany	RoHS compliant	REACH	

Split cable entry system for routing cables with connectors providing an IP54 / UL Type 12 rating. Routing, sealing and providing strain relief for cable diameters from 1 to 35 mm.

The cable entry system is easy to install. Cable grommets are placed into compartments and are securely fixed to the frame during assembly.

The KEL-U frames match exactly the cut-out dimensions for 10-, 16- and 24-pin standard industrial connectors. Either a cut-out of 36 mm or 46 mm in height can be chosen depending on the cables being routed. The KEL-U-B frame matches the cut-out dimensions of  $46 \times 46$  mm measuring instruments.

For tool-free assembly / disassembly of the cable entry frames the snap mounting frame KEL-SNAP can be used.

The single-row versions KEL-E are particularly suited for flat connectors. The small frames are ideal for applications with limited space.

A flat rubber gasket is included in the shipment.

### This product is available in different versions: With steel screws or stainless steel screws. It is also possible to integrate threaded bushings. Please ask us about your desired variant.

The version with threaded bushings enables the cable entry frame to be screwed onto the housing from the inside out. This protects against vandalism and tampering with the housing from the outside.

# **Specifications**

IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
lame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, UV-resistant, silicone free, anti-corrosive (V2A versions), halogen free
Mounting options	Snap-in with KEL-SNAP,Screw type mounting

Mounting height

KEL-U 24|10

17 mm

# Advantages & benefits

(EL-U 24 10	Part No.
	EAN
	Package quantity
$\circ \square \square \square \square \circ \square \circ$	For max. no. of cables
	Max. cable diameter
	Length

Width

**Product types & sizes** 

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material

Suitable for grommets

17 mm 17 mm 112 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 10 x KT small

#### KEL-U 24|10 V2A

	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54241.200 4251269315732 10 40 17 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Stainless steel (V2A) 10 x KT small
KEL-U 24 7	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54247 4251269315763 10 25 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 6 x KT small 1 x KT large
KEL-U 24 7 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54247.200 4251269315770 10 25 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Stainless steel (V2A) 6 x KT small 1 x KT large
KEL-U 24 4	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54244 4251269315749 10 6 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 2 x KT small 2 x KT large
KEL-U 24 4 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54244.200 4251269315756 10 6 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Stainless steel (V2A) 2 x KT small 2 x KT large
KEL-U 16 8	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54168 4251269315626 10 32 17 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 8 × KT small

Suitable for grommets

8 x KT small

KEL-U 16 8 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54168.200 4251269315633 10 32 17 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17mm 17mm 86 × 36mm 4 5,8mm Stainless steel (V2A) 8 x KT small
KEL-U 16 5	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54165 4251269315602 10 17 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 4 x KT small 1 x KT large
KEL-U 16 5 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54165.200 4251269315619 10 17 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Stainless steel (V2A) 4 x KT small 1 x KT large
KEL-U 16 2	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54162 4251269315589 10 2 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 2 x KT large
KEL-U 16 2 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54162.200 4251269315596 10 2 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Stainless steel (V2A) 2 x KT large
KEL-U 10 6	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54216 4251269315701 10 24 17 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 65 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 6 x KT small

	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54216.200 4251269315718 10 24 17 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17mm 17mm 65 × 36mm 4 5,8mm Stainless steel (V2A) 6 x KT small
KEL-U 10 3	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54212 4251269315688 10 9 35 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 65 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated 2 x KT small 1 x KT large
KEL-U 10 3 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54212.200 4251269315695 10 9 35 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 65 × 36 mm 4 5,8 mm Stainless steel (V2A) 2 x KT small 1 x KT large
KEL-U-B4	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54204 4251269315640 10 16 17 mm 73 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 46 × 46 mm 4 5,8 mm Mild steel, galvanically zinc plated 4 x KT small
KEL-U-B4 V2A	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54204.200 4251269315657 10 16 17 mm 73 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 46 × 46 mm 4 5,8 mm Stainless steel (V2A) 4 x KT small
KEL-U-B1	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	54206 4251269315664 10 1 35 mm 73 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 46 × 46 mm 4 5,8 mm Mild steel, galvanically zinc plated 1 × KT large

EV     Source of the second seco	KEL-U-B1 V2A	Part No.	54206.200	Height	17 mm
C       Pet kage quantity       10       Cut-out size       46 4 4 6 mm         Formax.no. rotables       35 mm       No. of acres holes       5,8 mm         Length       Max. calle diameter       35 mm       Statilities statilities (42,0)         Length       With       23 mm       Statilities (42,0)         Pet Max. calle diameter       20       No. of acres holes       1, x KT large         Nutb       Pet Max. calle diameter       10       No. of acres holes       12 are mm         Pet Max. calle diameter       10       No. of acres holes       13 mm       12 are mm         Vields       20       No. of acres holes       13 mm       2 are mm         Pet Max. calle diameter       17 mm       State holes holes       13 mm         Length       14 mm       State holes holes       13 mm       13 mm         State holes       10 mm       State holes holes       13 mm       13 mm         State holes       10 mm       State holes       13 mm       13 mm         State holes       10 mm       State holes       13 mm       13 mm         State holes       10 mm       State holes       13 mm       13 mm         State holes       10 mm       State holes				_	
C     For max, mo of cables     1     No. of screw holes     4       Max. cable diameter     35 mm     Size with a screw holes     5,6 mm       Width     59 mm     Size with a screw holes     1 x K1 args       Part No.     42250 mm     Size with a screw holes     1 x K1 args       Part No.     42250 mm     Size with a screw holes     2 mm       Max. cable diameter     10     Cubent after     1 mm       Part No.     42250 mm     Size with a screw holes     2 mm       Max. cable diameter     1 mm     Diam. of screw holes     2 mm       Max. cable diameter     1 mm     Diam. of screw holes     2 mm       Max. cable diameter     1 mm     Diam. of screw holes     3 mm       Size after holes     2 mm     Size after holes     2 mm       Midth     10     Cubent size     1 mm       Part No.     42250.2000 st3     Mounting holpit     17 mm       Part No.     42250.2000 st3     Mounting holpit     17 mm       Part No.     42250.2000 st3     Mounting holpit     17 mm       Part No.     42252.22030531     Mounting holpit     17 mm       Part No.     42252.22030531     Mounting holpit     17 mm       Part No.     42252.2000 st3     Mounting holpit     17 m					
C     Max. colled daneter     35 mm     Diam. of strew holes     5.8 mm       KEL-E5     Part No.     42250     Height     17 mm       Vidth     23 mm     Subble for grommels     1 x KT large       Vidth     23 mm     Subble for grommels     1 x KT large       Vidth     23 mm     Subble for grommels     1 x KT large       Vidth     23 mm     Subble for grommels     2 mm       Vidth     23 mm     Subble for grommels     2 mm       Vidth     23 mm     Subble for grommels     2 mm       Vidth     39 mm     Subble for grommels     2 mm       Vidth     39 mm     Subble for grommels     2 mm       Vidth     23 mm     Subble for grommels     2 mm       Vidth     39 mm     Subble for grommels     2 mm       Vidth     39 mm     Subble for grommels     5 mm					4
○       Import       73 mm       Screw material       Sciables steel (V2A)         ○       Width       58 mm       Suitable for grommals       Stables steel (V2A)         ○       Part No.       42250       Height       17 mm         ○       EAN       Additional steel       10       No. Stable for grommals       12 × 24 mm         ○       Part No.       4251269308376       Mounting height       12 × 24 mm       12 × 24 mm         Part No.       10       No. Stable for grommals       Sittable for grommals         Ø       Image       10       Additional steel       13 mm       Sittable for grommals       Sittable					
KI-15     Part No.     42250 423263908376     Height Mounting height No. of screw holes S. M.     17 mm Mounting height Mounting height Mounting height Mounting height Mounting height Mounting height Mounting height Mounting height Mill steel, galvanically since plated S. KT small       KI-15     Part No.     42250 Max. cabe diameter Length     42250 39 mm     Height Mounting height Mill steel, galvanically since plated S. KT small     17 mm Mill steel, galvanically since plated S. KT small       KIL-15 VIA mounting     Part No.     42250-200 Mill steel, galvanically since plated S. KT small     17 mm Mill steel, galvanically since plated S. KT small     17 mm Mill steel, galvanically since plated S. KT small       KIL-15 VIA mounting     Part No.     42250-200 Mill steel, galvanically since plated S. KT small     17 mm Mill steel, galvanically since plated S. KT small       KIL-15 VIA mounting     Part No.     42250-200 Mill steel, galvanically since plated S. KT small     17 mm Mill steel, galvanically since plated S. KT small       KIL-16 Mill mounting     Part No.     42250-200 Mill steel, galvanically since plated Mill steel, galvanicall					•
KI-53     Part No.     42250     Height     17 mm <ul> <li>Part No.</li> <li>Part No.</li></ul>		-			
Kit-E4     Part No.     42259     42259     Height Mounting height     17 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     11 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     11 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     10 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     10 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     10 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     10 mm       Max cable diameter     11 mm     11 mm     11 mm     11 mm     12 mm       Max cable diameter     11 mm     12 mm     12 mm     12 mm       Max cable diameter     11 mm     13 mm     5 mm     5 mm       Max cable diameter     11 mm     13 mm     5 mm     5 mm       Max cable diameter     11 mm     12 mm     5 mm     5 mm       Max cable diameter     12 mm     12 mm     5 mm     5 mm       Max cable diameter     12 mm     12 mm     5 mm     5 mm       Max cable diameter     12 mm     5 mm     5 mm       Max cable dia		VVIGUI	50 mm	Sultable for grommets	
Kit-E4     Part No.     42259     42259     Height Mounting height     17 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     11 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     11 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     10 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     10 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     10 mm       AKI - 54 V2A     Function of cables     10 mm     10 mm     10 mm     10 mm       Max cable diameter     11 mm     11 mm     11 mm     11 mm     12 mm       Max cable diameter     11 mm     12 mm     12 mm     12 mm       Max cable diameter     11 mm     13 mm     5 mm     5 mm       Max cable diameter     11 mm     13 mm     5 mm     5 mm       Max cable diameter     11 mm     12 mm     5 mm     5 mm       Max cable diameter     12 mm     12 mm     5 mm     5 mm       Max cable diameter     12 mm     12 mm     5 mm     5 mm       Max cable diameter     12 mm     5 mm     5 mm       Max cable dia					
Image: set of the set of th	KEL-E5	Part No.		•	17 mm
Image: Control of Cables     20     No. of Screw holes     2 2       Image: Control of Cables     17 mm     Diam. of Screw holes     3,8 mm       Image: Control of Cables     17 mm     Diam. of Screw holes     3,8 mm       Image: Control of Cables     17 mm     Diam. of Screw holes     5,8 mm       Image: Control of Cables     17 mm     Diam. of Screw holes     17 mm       Image: Control of Cables     17 mm     Diam. of Screw holes     17 mm       Image: Control of Cables     17 mm     Diam. of Screw holes     17 mm       Image: Control of Cables     10     Cut-out size     12 × 24 mm       Image: Control of Cables     17 mm     Diam. of Screw holes     5,8 mm       Image: Control of Cables     17 mm     Diam. of Screw holes     5,8 mm       Image: Control of Cables     17 mm     Diam. of Screw holes     5,8 mm       Image: Control of Cables     16     No. of Screw holes     5,8 mm       Image: Control of Cables     16     No. of Screw holes     2       Image: Control of Cables     16     No. of Screw holes     2       Image: Control of Cables     16     No. of Screw holes     2       Image: Control of Cables     16     No. of Screw holes     2       Image: Control of Cables     16     No. of Screw holes <th></th> <th></th> <th>4251269308376</th> <th>Mounting height</th> <th></th>			4251269308376	Mounting height	
Max. cable diameter Langth Width     17 mm 39 mm     Diam. of screw holes Screw material     5,8 mm plated     5,8 mm plated       KEL-55 V2A D     Part No: EAN Package quantity No. of screw holes     Part No: EAN Package quantity Package quantity No. of screw holes     17 mm Augustable for grommets     17 mm Screw material     17 mm Mounting height     17 mm Augustable for grommets       KEL-54 V2A D     Part No: EAN Package quantity Nuth     42259.200 4251269308433     Height Cut-out size No. of screw holes     12 Am Mounting height     17 mm Screw material       KEL-54 D     Part No: EAN Package quantity Nuth     42259 4251269308413     Height Cut-out size No. of screw holes     17 mm Screw material     17 mm Screw material       KEL-54 D     Part No: EAN Package quantity For max. no. of cables Max. cable diameter     4221569308413 10 Mounting height     17 mm Screw material     17 mm Mounting height     17 mm Mounting height       Vieth     Part No: EAN Package quantity For max. no. of cables Max. cable diameter     4221569308420 10 Mounting height     17 mm Screw holes     17 mm Screw holes     17 mm Screw holes       Vieth     Part No: EAN Package quantity Package quan		Package quantity	10	Cut-out size	112 × 24 mm
KEL-54 <ul> <li>Part No. Ength Mide diameter Length</li> </ul> 42259.200 425126930833 10 Cul-out size 20 Mounting height Cul-out size 112 × 24 mm Cul-out size 112 × 24 mm 112 × 24 mm Subable for grommets Subable for gr		For max. no. of cables	20	No. of screw holes	2
Width     39 mm     Suitable for grommets     plated       xtt-ts V2A     Part No.     42250.200     Height     17 mm       plated     4221269308383     Mounting height     17 mm       plated     Max. cable diameter     20     No. of screw holes     2       Max. cable diameter     147 mm     Screw material     Stainless steel (V2A)       Width     4221269308413     Height     17 mm       point     6     No.     42259       Width     4251269308413     Mounting height     17 mm       point     6     No.     5.8 mm       point     16     No. d screw holes     2.8 mm       Max. cable diameter     16     No. d screw holes     2.8 mm       Length     39 mm     Sortew material     Mild steel, galvanically zinc       plated     9 mm     50 mm     Screw material     Mild steel, galvanically zinc       plated     10 mm     39 mm     Screw material     Mild steel, galvanically zinc       plated     10 mm     39 mm     Screw material     M		Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
KIL-43 V2A     Part No.     42250.200 EAN     Height 4251269308383     Height Mounting height Cut-out size     17 mm 12 x 24 mm 7 mm <ul> <li></li></ul>		Length	147 mm	Screw material	Mild steel, galvanically zinc
KIL-5 V2A       Part No.       42250.200       Height       17 mm         Image: Constraint of the state of		Width	39 mm		plated
View     View     View     View       a     A     A     A     A       a     b     A     A     A       b     b     A     A     A       b     b     A     A     A       b     b     A     A     A       b     b     A     A     A       b     b     A     A     A       b     A     A     A     A       b     A     A     A     A       b     A     A     A     A       b     A     A     A     A       b     A     A     A     A       b     A     A     A     A       c     Cut-Out size     B     A     A       b     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     B     A				Suitable for grommets	5 x KT small
View     View     View     View       a     A     A     A     A       a     b     A     A     A       b     b     A     A     A       b     b     A     A     A       b     b     A     A     A       b     b     A     A     A       b     b     A     A     A       b     A     A     A     A       b     A     A     A     A       b     A     A     A     A       b     A     A     A     A       b     A     A     A     A       b     A     A     A     A       c     Cut-Out size     B     A     A       b     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     A     A     A     A       c     B     A					
Rel-E4 V2A       Part No.       42259.200       Height       17 mm         Vidth       39 mm       Suitable for grommets       5.8 mm         KEL-E4 V2A       Part No.       42259.200       Height       17 mm         Vidth       39 mm       Suitable for grommets       5.8 mm         KEL-E4 V2A       Part No.       42259.200       Height       17 mm         Vidth       39 mm       Suitable for grommets       5.8 mm         KEL-E4 V2A       Part No.       42259.200413       Mounting height       17 mm         Width       39 mm       Suitable for grommets       5.8 mm       17 mm         Vidth       39 mm       Suitable for grommets       5.8 mm       17 mm         Vidth       39 mm       Suitable for grommets       4 x KT small       17 mm         Vidth       39 mm       Suitable for grommets       4 x KT small       17 mm         Vidth       39 mm       Suitable for grommets       4 x KT small       17 mm         Vidth       39 mm       Suitable for grommets       4 x KT small       17 mm         Vidth       39 mm       Suitable for grommets       5.8 mm       17 mm         Vidth       39 mm       Suitable for grommets       4 x K	KEL-E5 V2A	Part No.	42250.200	Height	17 mm
For max, no. of cables     20     No. of screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Length     147 nm     Screw material     Stainless steel (V2A)       Width     39 mm     Suitable for grommets     5 x KT small       No. of screw holes     5,8 mm     Stainless steel (V2A)       Image: Screw material     Mounting height     17 mm       Image: Screw holes     17 mm     10       Image: Screw holes     17 mm       Image: Screw holes		EAN	4251269308383	Mounting height	17 mm
KEL-64     Vax. cable diameter Length     17 mm 147 mm 39 mm     Diam. of screw holes Screw material     5,8 mm Stainless steel (V2A)       KEL-64     Part No.     42259 4251269308413     Height Mounting height     17 mm 17 mm       Part No.     42259 4251269308413     Mounting height Mounting height     17 mm 17 mm       Part No.     42259 4251269308413     Mounting height Mounting height     17 mm 17 mm       Part No.     42259 4251269308413     Mounting height Mounting height     17 mm 17 mm       Part No.     42259 4251269308420     No. of screw holes Screw material     5,8 mm       Mild steel, galvanically zinc plated     10 4251269308420     Height Cut-out size Mounting height     17 mm 17 mm       Part No.     42259.200 4251269308420     Height Cut-out size Mounting height     17 mm 17 mm 120 mm     17 mm Screw material       Max. cable diameter Length     10 39 mm     No. of screw holes 120 nm     5,8 mm Screw material     17 mm 5,8 mm       Max. cable diameter Length     17 mm 120 nm     Screw material     17 mm 5,8 mm       Max. cable diameter Length     12 mm 39 mm     Suitable for grommets     5,8 mm 5,8 mm       Max. cable diameter Length     12 mm 39 mm     No d screw holes 5,8 mm     17 mm 5,8 mm       Midd steel, galvanically zinc Midd steel, galvanically zinc Midd steel, galvanically zinc Midd steel, galvanically zinc Midd steel, galvanically zinc     17 mm	0 <b> </b> 0	Package quantity	10	Cut-out size	112 × 24 mm
KEL-54     Part No.     42259 + 42252     Height is a stainless steel (V2A)       0     EAN     4221269308413     Mounting height is a stainless steel (V2A)       0     EAN     4221269308413     Mounting height is a stainless steel (V2A)       0     EAN     4221269308413     Mounting height is a stainless steel (V2A)       0     EAN     4251269308413     Mounting height is a stainless steel (V2A)       0     EAN     4251269308413     Mounting height is a stainless steel (V2A)       Max. cable diameter     16     No. of screw holes     5,8 mm       Length     120 mm     Screw material     Mild steel, galvanically zinc plated       Suitable for grommets     4 x KT small     17 mm       0     D     Cut-out size     86 × 24 mm       0     For max. no. of cables     16     No. of screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     2       10     Cut-out size     86 × 24 mm     17 mm       Package quantity     10     No. of screw holes     2       Midth     39 mm     Screw holes     2     86 × 24 mm       Vidth     39 mm     Screw holes     5,8 mm     5,8 mm       Suitable for grommets     4 x KT small     17 mm     17 mm       Vidth </td <td></td> <td>For max. no. of cables</td> <td>20</td> <td>No. of screw holes</td> <td>2</td>		For max. no. of cables	20	No. of screw holes	2
KEL-54     Part No.     42259     Height     17 mm       0     Package quantity     10     Cut-out size     86 x 24 mm       Part No.     4251269308413     Mounting height     17 mm       Package quantity     10     Cut-out size     86 x 24 mm       Package quantity     10     Diam. of screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Width     39 mm     Screw material     Mild steel, galvanically zinc plated       Width     39 mm     Suitable for grommets     4 x KT small       Image: Cut-out size     Fart No.     42259-200     Height     17 mm       Image: Cut-out size     Fart No.     42259-200     Height     17 mm       Image: Cut-out size     Fart No.     42259-200     Height     17 mm       Image: Cut-out size     Fart No.     42259-200     Height     17 mm       Image: Cut-out size     Fart No.     42259-200     Height     17 mm       Image: Cut-out size     Fart No.     42259-200     Height     17 mm       Image: Cut-out size     Fart No.     42259-200     Height     17 mm       Image: Cut-out size     Fart No.     4251269308420     Mounting height     17 mm       Image: Cut-out size<		Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
KEL-E4       Part No.       42259       Height       17 mm         Image: Description of the state of the s		Length	147 mm	Screw material	Stainless steel (V2A)
Fail No.       4253259308413       Mounting height       17 mm         Package quantity       10       Cut-out size       86 × 24 mm         Package quantity       10       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       120 mm       Screw material       Mild steel, galvanically zinc plated         Width       39 mm       Suitable for grommets       4 × KT small         Image: Control of the steel of the		Width	39 mm	Suitable for grommets	5 x KT small
Fail No.       4253259308413       Mounting height       17 mm         Package quantity       10       Cut-out size       86 × 24 mm         Package quantity       10       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       120 mm       Screw material       Mild steel, galvanically zinc plated         Width       39 mm       Suitable for grommets       4 × KT small         Image: Control of the steel of the					
EAN       4251269308413       Mounting height       17 mm         Package quantity       10       Cut-out size       86 × 24 mm         For max. no. of cables       16       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       120 mm       Screw material       Mild steel, galvanically zinc plated         Width       39 mm       Suitable for grommets       4 × KT small         Image: Control of Cables       16       No. of screw holes       17 mm         Suitable for grommets       4 × KT small       17 mm       17 mm         For max. no. of cables       16       No. of screw holes       2         For max. no. of cables       16       No. of screw holes       2         For max. no. of cables       16       No. of screw holes       2         For max. no. of cables       16       No. of screw holes       5,8 mm         Length       120 mm       Screw material       Stainless steel (V2A)         Width       39 mm       Suitable for grommets       4 × KT small         For max. no. of cables       120 mm       Screw material       5,8 mm         Length       120 mm       Suitable for grommets       5,8 mm </td <td>KEL-E4</td> <td>Part No.</td> <td>42259</td> <td>Height</td> <td>17 mm</td>	KEL-E4	Part No.	42259	Height	17 mm
Package quantity     10     Cut-out size     86 x 24 mm       For max. no. of cables     16     No. of screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Length     120 mm     Screw material     Mild steel, galvanically zinc plated       Width     39 mm     Screw material     plated       Mild steel, galvanically zinc plated     Suitable for grommets     4 x KT small		EAN	4251269308413		17 mm
For max. no. of cables     16     No. of screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Length     120 mm     Screw material     Mild steel, galvanically zinc plated       Width     39 mm     Screw material     Mild steel, galvanically zinc plated       Suitable for grommets     4 x KT small       Imax. cable diameter     17 mm     Diam. of screw holes       Imax. cable diameter     17 mm     17 mm       Imax. cable diameter     17 mm     10       Imax. cable diameter     17 mm     Diam. of screw holes     2       Imax. cable diameter     17 mm     Diam. of screw holes     2       Imax. cable diameter     17 mm     Diam. of screw holes     2       Imax. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Length     120 mm     Screw material     Stainless steel (V2A)       Imax. cable diameter     17 mm     Screw material     Stainless steel (V2A)       Imax. cable diameter     17 mm     Screw material     Stainless steel (V2A)       Imax. cable diameter     17 mm     Screw material     Stainless steel (V2A)       Imax. cable diameter     12 mm     Screw material     Stainless steel (V2A)       Imax. cable diameter     12 mm     Screw materia					86 × 24 mm
KEL-E4 V2A       Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Width       39 mm       Suitable for grommets       4 × KT small         Suitable for grommets       A × KT small       X × KT small         Max. cable diameter       42259.200       Height       17 mm         Part No.       4251269308420       Mounting height       17 mm         Package quantity       10       Cut-out size       86 × 24 mm         Package quantity       10       Cut-out size       5,8 mm         Max. cable diameter       17 mm       Diam. of screw holes       2         Max. cable diameter       17 mm       Screw material       Statiless steel (V2A)         Width       39 mm       Suitable for grommets       Statiless steel (V2A)         Vidth       10 mm       Screw material       4 × KT small         Max. cable diameter       12 mm       Mounting height       17 mm         Length       4251269308390       Mounting height       17 mm         Package quantity       10       Cut-out size       65 × 24 mm         Package quantity       10       Cut-out size       65 × 24 mm         Package quantity       10       No. of screw holes       2					
KEL-E4 V2A     Part No.     42259.200     Height     17 mm       Package quantity     10     Cut-out size     86 × 24 mm       For max. no. of cables     15     No. of screw holes     2       Width     10 mm     5crew material     Multiditely size       Width     10     Cut-out size     86 × 24 mm       Part No.     42259.200     Mounting height     17 mm       Package quantity     10     Cut-out size     86 × 24 mm       For max. no. of cables     16     No. of screw holes     2       Width     120 mm     Screw material     5km m       Width     120 mm     Screw material     4 x KT small       Width     120 mm     Screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Length     10     Cut-out size     65 × 24 mm       Vidth     10     Cut-out size     55 × 24 mm       Package quantity     10     Cut-out size     55 × 24 mm       For max. no. of cables     12     No. of screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Length     10     Screw material     5,8 mm       Wax. cable diameter     17 mm     Diam. of screw		Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
KEL-E3     Part No.     42258     Height     17 mm       Vidth     29 mm     Suitable for grommets     4 x KT small			120 mm		
KEL-E4 V2A       Part No.       42259.200       Height       17 mm         Package quantity       10       Cut-out size       86 × 24 mm         Package quantity       16       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       2         Width       39 mm       Screw material       Stainless steel (V2A)         Width       4251269308390       Mounting height       17 mm         Package quantity       10       Screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       120 mm       Screw material       Stainless steel (V2A)         Width       39 mm       Suitable for grommets       4 × KT small         Max       cable diameter       17 mm       17 mm         Package quantity       10       Cut-out size       65 × 24 mm         Max. cable diameter       12       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       2         Max. cable diame		-			
KEL-E3       Part No.       42258       Height       17 mm         View       Package quantity       10       Cut-out size       86 × 24 mm         View       Package quantity       10       Cut-out size       86 × 24 mm         Package quantity       10       Cut-out size       86 × 24 mm         For max. no. of cables       16       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       120 mm       Screw material       Stainless steel (V2A)         Width       39 mm       Suitable for grommets       4 x KT small         View       Parkage quantity       10       Cut-out size       65 × 24 mm         Package quantity       10       Cut-out size       65 × 24 mm         Package quantity       10       Cut-out size       65 × 24 mm         Package quantity       10       Cut-out size       65 × 24 mm         For max. no. of cables       12       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       98 mm       Screw material				Suitable for grommets	-
KEL-E3       Part No.       42258       Height       17 mm         View       Package quantity       10       Cut-out size       86 × 24 mm         View       Package quantity       10       Cut-out size       86 × 24 mm         Package quantity       10       Cut-out size       86 × 24 mm         For max. no. of cables       16       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       120 mm       Screw material       Stainless steel (V2A)         Width       39 mm       Suitable for grommets       4 x KT small         View       Parkage quantity       10       Cut-out size       65 × 24 mm         Package quantity       10       Cut-out size       65 × 24 mm         Package quantity       10       Cut-out size       65 × 24 mm         Package quantity       10       Cut-out size       65 × 24 mm         For max. no. of cables       12       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       98 mm       Screw material					
EAN       4251269308420       Mounting height       17 mm         Package quantity       10       Cut-out size       86 × 24 mm         For max. no. of cables       16       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       120 mm       Screw material       Stainless steel (V2A)         Width       39 mm       Suitable for grommets       4 x KT small         KEL-E3       Part No.       42258       Height       17 mm         Package quantity       10       Cut-out size       65 × 24 mm         Vidth       39 mm       Suitable for grommets       4 x KT small         Max. cable diameter       12       No. of screw holes       5,8 mm         EAN       4251269308390       Mounting height       17 mm         Package quantity       10       Cut-out size       65 × 24 mm         For max. no. of cables       12       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       98 mm       Screw material       Mild steel, galvanically zinc         Width       39 mm       Screw material       Mild steel, galvanically zinc <td>KEL-E4 V2A</td> <td>Part No.</td> <td>42259.200</td> <td>Height</td> <td>17 mm</td>	KEL-E4 V2A	Part No.	42259.200	Height	17 mm
•       •       •       •       86 × 24 mm         For max. no. of cables       16       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       120 mm       Screw material       Stainless steel (V2A)         Width       39 mm       Suitable for grommets       4 x KT small         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •       •       •         •       •       •					
For max. no. of cables       16       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       120 mm       Screw material       Stainless steel (V2A)         Width       39 mm       Suitable for grommets       4 x KT small         Vidth       42258       Height       17 mm         EAN       42258       Height       17 mm         Part No.       42258       Height       17 mm         Package quantity       10       Cut-out size       65 × 24 mm         Package quantity       10       Cut-out size       65 × 24 mm         For max. no. of cables       12       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       98 mm       Screw material       Mild steel, galvanically zinc         Width       39 mm       Screw material       Mild steel, galvanically zinc					
Max. cable diameter Length Width17 mm 120 mm 39 mmDiam. of screw holes Screw material Suitable for grommets5,8 mm Stainless steel (V2A) 4 x KT smallKEL-E3Part No.42258 EAN Package quantity For max. no. of cables Max. cable diameter Length WidthHeight 17 mm Cut-out size17 mm 65 × 24 mm 5,8 mmKEL-E3Part No.4251269308390 12 No. of screw holesMounting height 17 mm Cut-out size17 mm 65 × 24 mm 5,8 mm Mild steel, galvanically zinc plated					
Length Width120 mm 39 mmScrew material Suitable for grommetsStainless steel (V2A) 4 x KT smallKEL-E3Part No.42258Height17 mmPart No.4251269308390Mounting height17 mmPackage quantity10Cut-out size65 × 24 mmPackage quantity12No. of screw holes2For max. no. of cables12No. of screw holes5,8 mmMax. cable diameter17 mmDiam. of screw holes5,8 mmLength98 mmScrew materialMild steel, galvanically zinc plated					
KEL-E3       Part No.       42258       Height       17 mm         Image: Second condition of the second conditic conditic conditic condition of the second condition of the seco					•
KEL-E3       Part No.       42258       Height       17 mm         Image: Second sec		-			
Factor     42230     Regit     17 mm       EAN     4251269308390     Mounting height     17 mm       Package quantity     10     Cut-out size     65 × 24 mm       Por max. no. of cables     12     No. of screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Length     98 mm     Screw material     Mild steel, galvanically zinc       Width     39 mm     Screw material     plated					
Factor     42230     Regit     17 mm       EAN     4251269308390     Mounting height     17 mm       Package quantity     10     Cut-out size     65 × 24 mm       Por max. no. of cables     12     No. of screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Length     98 mm     Screw material     Mild steel, galvanically zinc       Width     39 mm     Screw material     plated					
Package quantity       10       Cut-out size       65 × 24 mm         For max. no. of cables       12       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       98 mm       Screw material       Mild steel, galvanically zinc         Width       39 mm       Screw material       plated	KEL-E3	Part No.	42258	Height	17 mm
For max. no. of cables       12       No. of screw holes       2         Max. cable diameter       17 mm       Diam. of screw holes       5,8 mm         Length       98 mm       Screw material       Mild steel, galvanically zinc         Width       39 mm       The steel state       plated		EAN	4251269308390	Mounting height	17 mm
For max. no. of cables     12     No. of screw holes     2       Max. cable diameter     17 mm     Diam. of screw holes     5,8 mm       Length     98 mm     Screw material     Mild steel, galvanically zinc       Width     39 mm     Total and the steel		Package quantity	10	Cut-out size	65 × 24 mm
Length98 mmScrew materialMild steel, galvanically zincWidth39 mmplated		For max. no. of cables	12	No. of screw holes	2
Width 39 mm plated		Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
		Length	98 mm	Screw material	Mild steel, galvanically zinc
Suitable for grommets 3 x KT small					
		Width	39 mm		plated

### KEL-E3 V2A



	Part No.	42258.200	Height	17 mm
	EAN	4251269308406	Mounting height	17 mm
	Package quantity	10	Cut-out size	65 × 24 mm
	For max. no. of cables	12	No. of screw holes	2
	Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
	Length	98 mm	Screw material	Stainless steel (V2A)
	Width	39 mm	Suitable for grommets	3 x KT small
KEL-E2	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42249 4251269308352 10 8 17 mm 73 mm 39 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 43 × 24 mm 2 5,8 mm Mild steel, galvanically zinc plated 2 x KT small
KEL-E2 V2A	Part No.	42249.200	Height	17 mm
	EAN	4251269308369	Mounting height	17 mm
	Package quantity	10	Cut-out size	43 × 24 mm
	For max. no. of cables	8	No. of screw holes	2
	Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
	Length	73 mm	Screw material	Stainless steel (V2A)
	Width	39 mm	Suitable for grommets	2 x KT small
KEL-E1	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	42261 4251269332500 10 4 17 mm 52 mm 39 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material Suitable for grommets	17 mm 17 mm 21 × 27 mm 2 5,8 mm Mild steel, galvanically zinc plated 1 x KT small
KEL-E1 V2A	Part No.	42261.200	Height	17 mm
	EAN	4251269333286	Mounting height	17 mm
	Package quantity	10	Cut-out size	21 × 27 mm
	For max. no. of cables	4	No. of screw holes	2
	Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
	Length	52 mm	Screw material	Stainless steel (V2A)
	Width	39 mm	Suitable for grommets	1 x KT small

icotek®