KEL-EMC-PF cable assembly bracket

for mounting individual shield clamps



The EMC bracket combined with the <u>matching PFS EMC shield clamp</u> is perfect in conjunction with the <u>KEL cable entry frame</u> for alleviating interferences due to shields.

The EMC clamp is assembled inside the control panel. For this process the fixing screws for the assembly of the KEL frame on the panel are used. A female screw thread M5 is already integrated in the KEL-EMC-PF bracket.

The KDR-EMC-PFM type can be mounted on icotek enclosure base plates with <u>slide frames KDR-ESR-VX25</u>.

Depending on the cable diameter, the corresponding PFS shield clamp can be snapped onto the EMC bracket.

Specifications

Material	Mild steel, galvanically zinc plated	Large surface contact between cable shield and housing, especially on conductive coated surfaces
Mounting options	Screw type mounting	Easily combines cable routing, EMC and strain relief due to the use of the same mounting holes
		M5 Mounting hole for earthing tape or PE connection
		Direct, easy and quick contact to the enclosure

Designed for high density applications

Advantages & benefits

Replacement for EMC cable glands, even for pre-terminated cables

Product types & sizes

EMC-PF 24	Part No.	39180	Mounting	13 mm
	EAN	4251269305	5	
		993	Suitable for	KEL-ER 24,
	Package	1	cable entry	KEL-ER-E5,
	quantity		systems:	KEL 24, KEL
	Length L1	140 mm		E5, KEL-U
	Length L2	130 mm		24, KEL-FG-
	Width	35 mm		E5, KEL-FA
	Height	13 mm		24, KEL-
				QUICK 24,
				KEL-QUICK-
				E5, KEL-BES
				24, KEL-BES
				S 24, KEL-
No/				DPZ 24, KEI
				DPZ-E, KEL-
				DPU 24, KE
				DPR 24, KE



Part No. EAN	39170 4251269305	Mounting height	13 mm
	986	Suitable for	KEL-ER 16,
Package	1	cable entry	KEL-ER-E4,
quantity		systems:	KEL 16, KEL-
Length L1	113 mm		E4, KEL-U
Length L2	103 mm		16, KEL-FA
Width	35 mm		16, KEL-
Height	13 mm		QUICK 16,
			KEL-QUICK-
			E4, KEL-BES
			16, KEL-BES-
			S 16, KEL-

DPZ 16, KEL-DPFR 16

KEL-BES-S 10

KEL-EMC-PF 10



Part No.	39160	Mounting	13 mm
EAN	4251269305	height	
	979	Suitable for	KEL-ER 10,
Package	1	cable entry	KEL-ER-E3,
quantity		systems:	KEL 10, KEL-
Length L1	93 mm		E3, KEL-U
Length L2	83 mm		10, KEL-FG-
Width	35 mm		E3, KEL-FA
Height	13 mm		10, MIS-E3 2,
			KEL-QUICK
			10, KEL-
			QUICK-E3,
			KEL-BES 10,

Part No. EAN	39150 4251269305	Mounting height	13 mm
	962	Suitable for	KEL-ER-B,
Package	1	cable entry	KEL-ER-E2,
quantity		systems:	KEL-B, KEL-
Length L1	68 mm		E2, KEL-U-B,
Length L2	58 mm		KEL-FG-E2,
Width	35 mm		KEL-QUICK-
Height	13 mm		B, KEL-
			QUICK-E2,
			KEL-DPZ-B



KEL-EMC-PF 183



Part No.	39190	Mounting	13 mm
EAN	4251269318	height	
	313	Suitable for	KEL 183, KEL
Package	1	cable entry	183-E
quantity		systems:	
Length L1	200 mm		
Length L2	95 mm		
Width	35 mm		
Height	13 mm		



Part No.	39181	Mounting	22 mm
EAN	4251269318	height	
	368	Suitable for	KEL-ER 24,
Package	1	cable entry	KEL 24, KEL-
quantity		systems:	U 24, KEL-FA
Length L1	140 mm		24, KEL-
Length L2	130 mm		QUICK 24,
Width	60 mm		KEL-BES 24,
Height	22 mm		KEL-BES-S
			24, KEL-DPZ
			24, KEL-DPU
			24, KEL-DPR
			24 161

24, KEL-DPFR 24

KEL-EMC-PFM 16



Part No.	39183	Mounting	22 mm
EAN	4251269318	height	
	344	Suitable for	KEL-ER 16,
Package	1	cable entry	KEL 16, KEL-
quantity		systems:	U 16, KEL-FA
Length L1	113 mm		16, KEL-
Length L2	103 mm		QUICK 16,
Width	60 mm		KEL-BES 16,
Height	22 mm		KEL-BES-S
			16, KEL-DPZ
			16, KEL-

DPFR 16

Part No. EAN	39184 4251269318	Mounting height	22 mm
	351	Suitable for	KEL-ER 10,
Package	1	cable entry	KEL 10, KEL-
quantity		systems:	U 10, KEL-FA
Length L1	93 mm		10, KEL-
Length L2	83 mm		QUICK 10,
Width	60 mm		KEL-BES 10,
Height	22 mm		KEL-BES-S
			10



KDR-EMC-PFM 24



Part No.	39191	Mounting	30,5 mm
EAN	4251269321	height	
	528	No. of screw	2
Package	1	holes	
quantity		Diam. of screw	5,5 mm
Length	140 mm	holes	
Length L2	130 mm	Suitable for	KDR-ESR-
Width	60 mm	cable entry	VX25, KDR-
Height	30,5 mm	systems:	VX25



Part No. EAN	39192 4251269321	Mounting height	30,5 mm
	535	No. of screw	2
Package	1	holes	
quantity		Diam. of screw	5,5 mm
Length	113 mm	holes	
Length L2	103 mm	Suitable for	KDR-ESR-
Width	60 mm	cable entry	VX25, KDR-
Height	30,5 mm	systems:	VX25

