KEL-ER CR split cable entry frames

for the use in cleanrooms / IP66 / UL Type 12/4X*



IP54	IP55	IP64	IP65	IP66
UL TYPE	UL TYPE	c FN ° us	RI≸Ħ	EN 45545-2
((())) EN 61373	ECOLAB certified	150 4892-2A	EN ISO 14644	PNEUMATICS
RoHS	REACH	Made in Germany		



Split cable entry system for routing and sealing cables with connectors, providing an IP66 / UL Type 12/4X* rating and strain relief for cable diameters from 1 to 16 mm (single-hole grommets KT CR 1 - 15) and 16 to 35 mm (single-hole grommets KT CR 16 - 34).

The cable entry system is easy to install. Cable grommets are placed into compartments and are securely fixed to the frame during assembly.

The KEL-ER CR frames match exactly the cut-out dimensions for 10-, 16- and 24pin standard industrial connectors. Either a cut-out of 36 mm or 46 mm in height can be chosen depending on the cables being routed. The KEL-ER-B CR frame matches the cut-out dimensions of 46 \times 46 mm measuring instruments.

The single-row versions KEL-ER-E CR are particularly suited for flat connectors. The small frames are ideal for applications with limited space.

A flat rubber gasket is included in the shipment.

The products with article ending .600 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1. The materials used for these products have been tested and certified for outgassing according to VOC/SVOC (ISO 14644-8; ISO 16000-6,-9,-11,-25, VDI 2083 sheet 17).

The products with the article ending .601 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1.

*4X for indoor use only

Advantages & benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Strain relief according to EN 62444
- High stability, vibration resistant
- Space-saving shape

Specifications

IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66
UL Type (UL 50E)	UL Type 12, UL Type 4X*
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, UV-resistant, silicone free, anti-corrosive (V2A versions), halogen free
Mounting options	Screw type mounting
Mounting height	17 mm

Product types & sizes







(5)VUC				
	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48244.600 4251269325762 5 4 35 mm 147 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 112 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated ja 2 x KT small 2 x KT large
KEL-ER 16 8 CR	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48168.601 4251269325847 5 8 16 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated nein 8 x KT small
KEL-ER 16 8 CR (S)VOC	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48168.600 4251269325700 5 8 16 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated ja 8 x KT small
KEL-ER 16 5 CR	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48165.601 4251269325830 5 5 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated nein 4 x KT small 1 x KT large
KEL-ER 16 5 CR (S)VOC	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48165.600 4251269325694 5 5 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated ja 4 x KT small 1 x KT large

KEL-ER 16|2 CR



0 0	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48162.601 4251269325823 5 2 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated nein 2 x KT large
KEL-ER 16 2 CR (5)VOC	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48162.600 4251269325687 5 2 35 mm 120 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 86 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated ja 2 x KT large
KEL-ER 10/6 CR	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48216.601 4251269325885 5 6 16 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 65 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated nein 6 x KT small
KEL-ER 10/6 CR (S)VOC	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48216.600 4251269325748 5 6 16 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 65 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated ja 6 x KT small
KEL-ER 10 3 CR	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48212.601 4251269325878 5 3 35 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 65 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated nein 2 x KT small 1 x KT large

	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48212.600 4251269325731 5 3 35 mm 98 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 65 × 36 mm 4 5,8 mm Mild steel, galvanically zinc plated ja 2 x KT small 1 x KT large
KEL-ER-B4 CR	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48204.601 4251269325854 5 4 16 mm 73 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 46 × 46 mm 4 5,8 mm Mild steel, galvanically zinc plated nein 4 x KT small
KEL-ER-B4 CR (S)VOC	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48204.600 4251269325717 5 4 16 mm 73 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 46 × 46 mm 4 5,8 mm Mild steel, galvanically zinc plated ja 4 x KT small
KEL-ER-B1 CR	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48206.601 4251269325861 5 1 35 mm 73 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 46 × 46 mm 4 5,8 mm Mild steel, galvanically zinc plated nein 1 x KT large
KEL-ER-B1 CR (S)VOC	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48206.600 4251269325724 5 1 35 mm 73 mm 58 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17 mm 17 mm 46 × 46 mm 4 5,8 mm Mild steel, galvanically zinc plated ja 1 x KT large

KEL-ER-E5 CR



KEL-ER-E3 CR (S)VOC



	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	48258.600 4251269325809 5 3 16 mm 98 mm 39 mm	Height Mounting height No. of screw holes Diam. of screw holes Screw material (S)VOC tested Suitable for grommets	17mm 17mm 2 5,8mm Mild steel, galvanically zinc plated ja 3 x KT small
EL-ER-E2 CR	Part No.	48249.601	Height	17 mm
	EAN	4251269325922	Mounting height	17 mm
	Package quantity	5	Cut-out size	43 × 24 mm
	For max. no. of cables	2	No. of screw holes	2
	Max. cable diameter	16 mm	Diam. of screw holes	5,8 mm
	Length	73 mm	Screw material	Mild steel, galvanically zinc
	Width	39 mm		plated
			(S)VOC tested	nein
			Suitable for grommets	2 x KT small
EL-ER-E2 CR (S)VOC	Part No.	48249.600	Height	17 mm
	EAN	4251269325786	Mounting height	17 mm
	Package quantity	5	Cut-out size	43 × 24 mm
	For max. no. of cables	2	No. of screw holes	2
	Max. cable diameter	16 mm	Diam. of screw holes	5,8 mm
	Length	73 mm	Screw material	Mild steel, galvanically zinc
	Width	39 mm		plated
			(S)VOC tested	ja
			Suitable for grommets	2 x KT small

