KEL-SNAP | Mounting frames

for tool-free snap-in mounting of cable entry frames / IP54 / UL Type 12



The patented KEL-SNAP frame provides a quick snap-in assembly of the <u>KEL</u> / <u>KEL-</u> <u>U</u> / <u>KEL-QUICK</u> / <u>KEL-FG-A</u> cable entry systems.

Control panels, cabinets or machines can be equipped with the KEL-SNAP frame at delivery, allowing a simple push in of the KEL frame when routing the cables and conduits. Perfect for enclosures that are maintenance intensive or for an install at a later date.

icotek is also offering the snap-in frame as splittable version KEL-SNAP-S in various sizes that makes a subsequent assembly possible.

There's also a <u>blank plate BPK-SNAP</u> available to close cut-outs of pre-assembled KEL-SNAP frames.

A cut-out of 46 mm also can be chosen instead of 36 mm. Thus prefabricated multi-pin connectors can be used.

Specifications

IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	silicone free, halogen free
Mounting options	Screw type mounting
Mounting height	38 mm

Advantages & benefits

- Upon disassembly (e.g. maintenance) screwing and unscrewing of the cable entry frame is not necessary
- Drilling template identical to cable entry frame (except KEL-SNAP-B)
- Integrated gasket
- Previously assembled cable harnesses are quickly and easily attached
- KEL-SNAP-S: Subsequent assembly possible
- KEL-SNAP-S: There is no need to thread the cables through the snap-on frame as the divisible frame can be snapped together when the lines have already been passed through the cut-out

Product types & sizes



Part No.	42042	Cut-out size	112 × 36 mm
EAN	4251269307	No. of screw	4
	652	holes	
Package	10	Diam. of screw	5,5 mm
quantity		holes	
Length	155 mm	Suitable for	KEL 24, KEL-
Width	64 mm	cable entry	U 24, KEL-
Height	38 mm	systems:	QUICK 24,
Mounting	38 mm		KEL-FA 24,
height			KEL-FG-A
		Split	No



Part No. EAN	42044 4251269307 669	Cut-out size No. of screw holes	112 × 66 mm 4
Package quantity	1	Diam. of screw holes	5,5 mm
Length Width Height	155 mm 89 mm 38 mm	Suitable for cable entry systems:	KEL 24-E
Mounting height	38 mm	Split	Νο

KEL-SNAP 24-MT



Part No.	42046	Cut-out size	112 × 82 mm
EAN	4251269307	No. of screw	6
	676	holes	
Package	1	Diam. of screw	5,5 mm
quantity		holes	
Length	155 mm	Suitable for	KEL 24-MT
Width	108 mm	cable entry	
Height	38 mm	systems:	
Mounting	38 mm	Split	No
height			

KEL-SNAP 16



Part No. EAN	42040 4251269307 645	Cut-out size No. of screw holes	86 × 36 mm 4
Package guantity	10	Diam. of screw	5,5 mm
Length	128 mm	Suitable for	KEL 16, KEL-
Width Height	64 mm 38 mm	cable entry systems:	U 16, KEL-FA 16, KEL-
Mounting height	38 mm	Split	QUICK 16 No



Part No. EAN	42039 4251269307 638	Cut-out size No. of screw holes	65 × 36 mm 4
Package quantity	10	Diam. of screw	5,5 mm
Length	108 mm	Suitable for	KEL 10, KEL-
Width	64 mm	cable entry	U 10, KEL-FA
Height	38 mm	systems:	10, KEL-
Mounting	38 mm		QUICK 10
height		Split	No

KEL-SNAP-B



Part No. FAN	42038 4251269307	Cut-out size	46 × 46 mm 4
EAN	4231209307 621	holes	4
Package quantity	10	Diam. of screw holes	5,5 mm
Length Width Height Mounting height	81 mm 64 mm 38 mm 38 mm	Suitable for cable entry systems: Split	KEL-B, KEL- U-B, KEL- QUICK-B No

KEL-SNAP-S 24



Part No.	42060	Cut-out size	112 × 36 mm
EAN	4251269323	No. of screw	4
	720	holes	
Package	10	Diam. of screw	5,5 mm
quantity		holes	
Length	155 mm	Suitable for	KEL 24, KEL-
Width	64 mm	cable entry	U 24, KEL-
Height	38 mm	systems:	QUICK 24,
Mounting	38 mm		KEL-FA 24,
height			KEL-FG-A
		Split	Yes



Part No. EAN	42061 4251269323 737	Cut-out size No. of screw holes	86 × 36 mm 4
Package quantity	10	Diam. of screw holes	5,5 mm
Length	128 mm	Suitable for	KEL 16, KEL-
Width	64 mm	cable entry	U 16, KEL-FA
Height	38 mm	systems:	16, KEL-
Mounting	38 mm		QUICK 16
height		Split	Yes

KEL-SNAP-S 10



Part No.	42062	Cut-out size	65 × 36 mm
EAN	4251269323	No. of screw	4
	744	holes	
Package	10	Diam. of screw	5,5 mm
quantity		holes	
Length	108 mm	Suitable for	KEL 10, KEL-
Width	64 mm	cable entry	U 10, KEL-FA
Height	38 mm	systems:	10, KEL-
Mounting	38 mm		QUICK 10
height		Split	Yes

KEL-SNAP-S-B



Part No. EAN	42063 4251269323 751	Cut-out size No. of screw holes	46 × 46 mm 4
Package quantity	10	Diam. of screw holes	5,5 mm
Length	81 mm	Suitable for	KEL-B, KEL-
Width	64 mm	cable entry	U-B, KEL-
Height	38 mm	systems:	QUICK-B
Mounting height	38 mm	Split	Yes

