

KT-DPF | Multi-range cable grommets, black

in pyramid shape, for cable diameters 3-26 mm / IP54



IP54



ECOLAB
certified



RoHS
compliant



Made in
Germany

The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

Black KT-DPF grommets have an increased chemical resistance, e.g. against aggressive oils, coolants etc.

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

It is recommended that additional strain relief be provided for the cables using a cable tie.

Cutting of KT-DPF grommets: Cable diameter less 20%.

Specifications


IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-HB
Operating temperature	-30 C° to 90 C°
Properties	higher chemical resistance

Advantages & benefits

- Large clamping range of 3 to 26 mm with only 3 grommets
- Ideal for wiring non pre-terminated cables locally
- Easy storage

Product types & sizes


KT-DPF-A bk



Part No.	41360
EAN	4251269307102
Package quantity	10
For max. no. of cables	1
Colour	black
Length	21 mm
Width	21 mm


Height	50 mm
Mounting height	33 mm
Clamping range	3 - 12 mm
Clamping range	1 x 3 - 12 mm

KT-DPF-B bk



Part No.	41361
EAN	4251269307119
Package quantity	10
For max. no. of cables	1
Colour	black
Length	41,5 mm
Width	42 mm

Height	59 mm
Mounting height	42 mm
For cable type	Round cable
Clamping range	4 - 18 mm
Clamping range	1 x 4 - 18 mm



Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41362
4251269307126
10
1
black
41,5 mm
42 mm

Height
Mounting height
For cable type
Clamping range
Clamping range

59 mm
42 mm
Round cable
14 - 26 mm
1 x 14 - 26 mm