


KEL-DPZ CR multi-membrane cable entry plates, round

for the use in cleanrooms, M25 - M63 / IP66 / IP68 / UL Type 12/4X*



KEL-DPZ CR round cable entry plates are designed to route and seal cables without connectors or fibre optics (from 1.5 mm to 22 mm in diameter) in limited space.

The assembly of the KEL-DPZ CR round with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ CR round provides strain relief and protection IP66 / IP68 / UL Type 4X*.

The round versions of the KEL-DPZ CR series have a thread to fit in metric cut-outs from M25 to M63. Thus cut-outs for metric cable glands can be used.

The products with article ending .600 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1. The materials used for these products have been tested and certified for outgassing according to VOC/SVOC (ISO 14644-8; ISO 16000-6,-9,-11,-25, VDI 2083 sheet 17).

The products with the article ending .601 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1.

*4X for indoor use only

Specifications


IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
UL Type (UL 50E)	UL Type 12, UL Type 4X*
Material	Elastomer Base frame: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free
Mounting options	Fasten with locknut

Advantages & Benefits

- Fast mounting
- High cable density
- Certified protection IP66/IP68 (acc. to EN 60529)
- Automatic sealing and strain relief for the cable
- Suitable for metric cut-outs
- Hexagonal locknut included in the delivery
- Hygienic design - free of dirt-collecting recesses







Product Types & Sizes







KEL-DPZ 25|3 CR gy




Part No.	43736.601
EAN	4251269328268
Package quantity	5
For max. no. of cables	3
Max. cable diameter	6,5 mm
Color	gray (similar RAL 7035)
Height	22 mm

Mounting height	8 mm
External diameter	39 mm
Cut-out size, round	25,3 mm
Cut-out size, metric	M25
Thread	M25 x 1,5
Thread length	14 mm
(S)VOC tested	nein
Clamping range	2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm


KEL-DPZ 25 3 CR (S)VOC gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	43736.600 4251269327964 5 3 6,5 mm gray (similar RAL 7035) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 39 mm 25,3 mm M25 M25 × 1,5 14 mm ja 2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm
KEL-DPZ 25 3 CR bk 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	50736.601 4251269328411 5 3 6,5 mm black 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 39 mm 25,3 mm M25 M25 × 1,5 14 mm nein 2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm
KEL-DPZ 25 3 CR (S)VOC bk 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	50736.600 4251269328114 5 3 6,5 mm black 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 39 mm 25,3 mm M25 M25 × 1,5 14 mm ja 2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm
KEL-DPZ 25 4 CR gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	43737.601 4251269328275 5 4 5,2 mm gray (similar RAL 7035) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 39 mm 25,3 mm M25 M25 × 1,5 14 mm nein 4 x 3.2 - 5.2 mm
KEL-DPZ 25 4 CR (S)VOC gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	43737.600 4251269327971 5 4 5,2 mm gray (similar RAL 7035) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 39 mm 25,3 mm M25 M25 × 1,5 14 mm ja 4 x 3.2 - 5.2 mm
KEL-DPZ 25 4 CR bk 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	50737.601 4251269328428 5 4 5,2 mm black 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 39 mm 25,3 mm M25 M25 × 1,5 14 mm nein 4 x 3.2 - 5.2 mm

KEL-DPZ 25 4 CR (S)VOC bk 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	50737.600 4251269328121 5 4 5,2 mm black 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 39 mm 25,3 mm M25 M25 × 1,5 14 mm ja 4 x 3.2 - 5.2 mm
KEL-DPZ 32 4 CR gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	43732.601 4251269328237 5 4 12,5 mm gray (similar RAL 7035) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 44 mm 32,3 mm M32 M32 × 1,5 14 mm nein 3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm
KEL-DPZ 32 4 CR (S)VOC gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	43732.600 4251269327933 5 4 12,5 mm gray (similar RAL 7035) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 44 mm 32,3 mm M32 M32 × 1,5 14 mm ja 3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm
KEL-DPZ 32 4 CR bk 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	50732.601 4251269328381 5 4 12,5 mm black 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 44 mm 32,3 mm M32 M32 × 1,5 14 mm nein 3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm
KEL-DPZ 32 4 CR (S)VOC bk 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	50732.600 4251269328084 5 4 12,5 mm black 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 44 mm 32,3 mm M32 M32 × 1,5 14 mm ja 3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm
KEL-DPZ 32 4-2 CR gy 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	43733.601 4251269328244 5 4 9,5 mm gray (similar RAL 7035) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length (S)VOC tested Clamping range	8 mm 44 mm 32,3 mm M32 M32 × 1,5 14 mm nein 4 x 5 - 9.5 mm




Part No. **43733.600**
EAN **4251269327940**
Package quantity **5**
For max. no. of cables **4**
Max. cable diameter **9,5 mm**
Color **gray (similar RAL 7035)**
Height **22 mm**

Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **4 x 5 - 9.5 mm**




Part No. **50733.601**
EAN **4251269328398**
Package quantity **5**
For max. no. of cables **4**
Max. cable diameter **9,5 mm**
Color **black**
Height **22 mm**

Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
(S)VOC tested **nein**
Clamping range **4 x 5 - 9.5 mm**




Part No. **50733.600**
EAN **4251269328091**
Package quantity **5**
For max. no. of cables **4**
Max. cable diameter **9,5 mm**
Color **black**
Height **22 mm**

Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **4 x 5 - 9.5 mm**




Part No. **43734.601**
EAN **4251269328251**
Package quantity **5**
For max. no. of cables **7**
Max. cable diameter **6,5 mm**
Color **gray (similar RAL 7035)**
Height **22 mm**

Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
(S)VOC tested **nein**
Clamping range **7 x 3.2 - 6.5 mm**



Part No. **43734.600**
EAN **4251269327957**
Package quantity **5**
For max. no. of cables **7**
Max. cable diameter **6,5 mm**
Color **gray (similar RAL 7035)**
Height **22 mm**


Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **7 x 3.2 - 6.5 mm**



Part No. **50734.601**
EAN **4251269328404**
Package quantity **5**
For max. no. of cables **7**
Max. cable diameter **6,5 mm**
Color **black**
Height **22 mm**


Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
(S)VOC tested **nein**
Clamping range **7 x 3.2 - 6.5 mm**

KEL-DPZ 32|7 CR
(S)VOC bk




Part No.	50734.600	Mounting height	8 mm
EAN	4251269328107	External diameter	44 mm
Package quantity	5	Cut-out size, round	32,3 mm
For max. no. of cables	7	Cut-out size, metric	M32
Max. cable diameter	6,5 mm	Thread	M32 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	7 x 3.2 - 6.5 mm

KEL-DPZ 40|8 CR gy




Part No.	43741.601	Mounting height	8 mm
EAN	4251269328282	External diameter	52 mm
Package quantity	5	Cut-out size, round	40,4 mm
For max. no. of cables	8	Cut-out size, metric	M40
Max. cable diameter	10,2 mm	Thread	M40 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm

KEL-DPZ 40|8 CR
(S)VOC gy




Part No.	43741.600	Mounting height	8 mm
EAN	4251269327988	External diameter	52 mm
Package quantity	5	Cut-out size, round	40,4 mm
For max. no. of cables	8	Cut-out size, metric	M40
Max. cable diameter	10,2 mm	Thread	M40 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm

KEL-DPZ 40|8 CR bk




Part No.	50741.601	Mounting height	8 mm
EAN	4251269328435	External diameter	52 mm
Package quantity	5	Cut-out size, round	40,4 mm
For max. no. of cables	8	Cut-out size, metric	M40
Max. cable diameter	10,2 mm	Thread	M40 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm


KEL-DPZ 40|8 CR
(S)VOC bk




Part No.	50741.600	Mounting height	8 mm
EAN	4251269328138	External diameter	52 mm
Package quantity	5	Cut-out size, round	40,4 mm
For max. no. of cables	8	Cut-out size, metric	M40
Max. cable diameter	10,2 mm	Thread	M40 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm

KEL-DPZ 50|8 CR gy


Part No.	43750.601	Mounting height	8 mm
EAN	4251269328299	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	8	Cut-out size, metric	M50
Max. cable diameter	12,5 mm	Thread	M50 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	5 x 5 - 10.2 mm 3 x 7.2 - 12.5 mm

KEL-DPZ 50|8 CR (S)VOC gy


Part No.	43750.600	Mounting height	8 mm
EAN	4251269327995	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	8	Cut-out size, metric	M50
Max. cable diameter	12,5 mm	Thread	M50 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	5 x 5 - 10.2 mm 3 x 7.2 - 12.5 mm

KEL-DPZ 50|8 CR bk

Part No.	50750.601	Mounting height	8 mm
EAN	4251269328442	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	8	Cut-out size, metric	M50
Max. cable diameter	12,5 mm	Thread	M50 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	5 x 5 - 10.2 mm 3 x 7.2 - 12.5 mm


KEL-DPZ 50|8 CR (S)VOC bk

Part No.	50750.600	Mounting height	8 mm
EAN	4251269328145	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	8	Cut-out size, metric	M50
Max. cable diameter	12,5 mm	Thread	M50 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	5 x 5 - 10.2 mm 3 x 7.2 - 12.5 mm

KEL-DPZ 50|10 CR gy

Part No.	43751.601	Mounting height	8 mm
EAN	4251269328305	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	10	Cut-out size, metric	M50
Max. cable diameter	22,2 mm	Thread	M50 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	7 x 3.2 - 6.5 mm 2 x 5 - 10.2 mm 1 x 16 - 22.2 mm


**KEL-DPZ 50|10 CR
(S)VOC gy**



Part No. **43751.600**
EAN **4251269328008**
Package quantity **5**
For max. no. of cables **10**
Max. cable diameter **22,2 mm**
Color **gray (similar RAL 7035)**
Height **22 mm**

Mounting height
External diameter **62 mm**
Cut-out size, round **50,4 mm**
Cut-out size, metric **M50**
Thread **M50 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **7 × 3.2 - 6.5 mm**
2 × 5 - 10.2 mm
1 × 16 - 22.2 mm


KEL-DPZ 50|10 CR bk



Part No. **50751.601**
EAN **4251269328459**
Package quantity **5**
For max. no. of cables **10**
Max. cable diameter **22,2 mm**
Color **black**
Height **22 mm**

Mounting height
External diameter **62 mm**
Cut-out size, round **50,4 mm**
Cut-out size, metric **M50**
Thread **M50 × 1,5**
Thread length **14 mm**
(S)VOC tested **nein**
Clamping range **7 × 3.2 - 6.5 mm**
2 × 5 - 10.2 mm
1 × 16 - 22.2 mm


**KEL-DPZ 50|10 CR
(S)VOC bk**



Part No. **50751.600**
EAN **4251269328152**
Package quantity **5**
For max. no. of cables **10**
Max. cable diameter **22,2 mm**
Color **black**
Height **22 mm**

Mounting height
External diameter **62 mm**
Cut-out size, round **50,4 mm**
Cut-out size, metric **M50**
Thread **M50 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **7 × 3.2 - 6.5 mm**
2 × 5 - 10.2 mm
1 × 16 - 22.2 mm


KEL-DPZ 50|12 CR gy



Part No. **43752.601**
EAN **4251269328312**
Package quantity **5**
For max. no. of cables **12**
Max. cable diameter **10,2 mm**
Color **gray (similar RAL 7035)**
Height **22 mm**

Mounting height
External diameter **62 mm**
Cut-out size, round **50,4 mm**
Cut-out size, metric **M50**
Thread **M50 × 1,5**
Thread length **14 mm**
(S)VOC tested **nein**
Clamping range **4 × 3.2 - 6.5 mm**
8 × 5 - 10.2 mm


**KEL-DPZ 50|12 CR
(S)VOC gy**



Part No. **43752.600**
EAN **4251269328015**
Package quantity **5**
For max. no. of cables **12**
Max. cable diameter **10,2 mm**
Color **gray (similar RAL 7035)**
Height **22 mm**


Mounting height
External diameter **62 mm**
Cut-out size, round **50,4 mm**
Cut-out size, metric **M50**
Thread **M50 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **4 × 3.2 - 6.5 mm**
8 × 5 - 10.2 mm

KEL-DPZ 50|12 CR bk




Part No.	50752.601	Mounting height	8 mm
EAN	4251269328466	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	12	Cut-out size, metric	M50
Max. cable diameter	10,2 mm	Thread	M50 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	4 x 3.2 - 6.5 mm

KEL-DPZ 50|12 CR (S)VOC bk




Part No.	50752.600	Mounting height	8 mm
EAN	4251269328169	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	12	Cut-out size, metric	M50
Max. cable diameter	10,2 mm	Thread	M50 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 6.5 mm

KEL-DPZ 50|19 CR gy




Part No.	43758.601	Mounting height	8 mm
EAN	4251269328336	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	19	Cut-out size, metric	M50
Max. cable diameter	6,5 mm	Thread	M50 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	19 x 3.2 - 6.5 mm

KEL-DPZ 50|19 CR (S)VOC gy




Part No.	43758.600	Mounting height	8 mm
EAN	4251269328039	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	19	Cut-out size, metric	M50
Max. cable diameter	6,5 mm	Thread	M50 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	19 x 3.2 - 6.5 mm

KEL-DPZ 50|19 CR bk




Part No.	50758.601	Mounting height	8 mm
EAN	4251269328480	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	19	Cut-out size, metric	M50
Max. cable diameter	6,5 mm	Thread	M50 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	19 x 3.2 - 6.5 mm

KEL-DPZ 50|19 CR (S)VOC bk



Part No.	50758.600	Mounting height	8 mm
EAN	4251269328183	External diameter	62 mm
Package quantity	5	Cut-out size, round	50,4 mm
For max. no. of cables	19	Cut-out size, metric	M50
Max. cable diameter	6,5 mm	Thread	M50 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	19 x 3.2 - 6.5 mm


KEL-DPZ 50|78 CR gy

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

43756.601
4251269328329
5
78
5 mm
gray (similar RAL 7035)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
nein
76 x 1.5 - 2.6 mm
2 x 2.5 - 5 mm


KEL-DPZ 50|78 CR (S)VOC gy

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

43756.600
4251269328022
5
78
5 mm
gray (similar RAL 7035)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
ja
76 x 1.5 - 2.6 mm
2 x 2.5 - 5 mm


KEL-DPZ 50|78 CR (S)VOC bk

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

50756.600
4251269328176
5
78
5 mm
black
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
ja
76 x 1.5 - 2.6 mm
2 x 2.5 - 5 mm


KEL-DPZ 50|78 CR bk

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

50756.601
4251269328473
5
78
5 mm
black
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
nein
76 x 1.5 - 2.6 mm
2 x 2.5 - 5 mm

KEL-DPZ 63|9 CR gy


Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

43760.601
4251269328343
5
9
22,2 mm
gray (similar RAL 7035)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
(S)VOC tested
Clamping range

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
nein
1 x 3.2 - 6.5 mm
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ 63|9 CR
(S)VOC gy



Part No. **43760.600**
EAN **4251269328046**
Package quantity **5**
For max. no. of cables **9**
Max. cable diameter **22,2 mm**
Color **gray (similar RAL 7035)**
Height **22 mm**

Mounting height
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **1 x 3.2 - 6.5 mm**
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ 63|9 CR bk



Part No. **50760.601**
EAN **4251269328497**
Package quantity **5**
For max. no. of cables **9**
Max. cable diameter **22,2 mm**
Color **black**
Height **22 mm**

Mounting height
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **14 mm**
(S)VOC tested **nein**
Clamping range **1 x 3.2 - 6.5 mm**
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ 63|9 CR
(S)VOC bk



Part No. **50760.600**
EAN **4251269328190**
Package quantity **5**
For max. no. of cables **9**
Max. cable diameter **22,2 mm**
Color **black**
Height **22 mm**

Mounting height
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **14 mm**
(S)VOC tested **ja**
Clamping range **1 x 3.2 - 6.5 mm**
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ 63|13 CR gy



Part No. **43761.601**
EAN **4251269328350**
Package quantity **5**
For max. no. of cables **13**
Max. cable diameter **16,2 mm**
Color **gray (similar RAL 7035)**
Height **22 mm**


Mounting height
External diameter **75 mm**
Cut-out size, round **63,4 mm**
Cut-out size, metric **M63**
Thread **M63 × 1,5**
Thread length **14 mm**
(S)VOC tested **nein**
Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm

KEL-DPZ 63|13 CR
(S)VOC gy




Part No.	43761.600	Mounting height	8 mm
EAN	4251269328053	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	13	Cut-out size, metric	M63
Max. cable diameter	16,2 mm	Thread	M63 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 5 x 9 - 16.2 mm

KEL-DPZ 63|13 CR bk




Part No.	50761.601	Mounting height	8 mm
EAN	4251269328503	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	13	Cut-out size, metric	M63
Max. cable diameter	16,2 mm	Thread	M63 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 5 x 9 - 16.2 mm

KEL-DPZ 63|13 CR
(S)VOC bk




Part No.	50761.600	Mounting height	8 mm
EAN	4251269328206	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	13	Cut-out size, metric	M63
Max. cable diameter	16,2 mm	Thread	M63 × 1,5
Color	black	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 5 x 9 - 16.2 mm

KEL-DPZ 63|14 CR gy





Part No.	43762.601	Mounting height	8 mm
EAN	4251269328367	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	14	Cut-out size, metric	M63
Max. cable diameter	10,2 mm	Thread	M63 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	nein
		Clamping range	14 x 5 - 10.2 mm


KEL-DPZ 63|14 CR
(S)VOC gy





Part No.	43762.600	Mounting height	8 mm
EAN	4251269328060	External diameter	75 mm
Package quantity	5	Cut-out size, round	63,4 mm
For max. no. of cables	14	Cut-out size, metric	M63
Max. cable diameter	10,2 mm	Thread	M63 × 1,5
Color	gray (similar RAL 7035)	Thread length	14 mm
Height	22 mm	(S)VOC tested	ja
		Clamping range	14 x 5 - 10.2 mm


KEL-DPZ 63 14 CR bk 	Part No.	50762.601	Mounting height	8 mm
	EAN	4251269328510	External diameter	75 mm
	Package quantity	5	Cut-out size, round	63,4 mm
	For max. no. of cables	14	Cut-out size, metric	M63
	Max. cable diameter	10,2 mm	Thread	M63 × 1,5
	Color	black	Thread length	14 mm
	Height	22 mm	(S)VOC tested	nein
			Clamping range	14 x 5 - 10.2 mm

KEL-DPZ 63 14 CR (S)VOC bk 	Part No.	50762.600	Mounting height	8 mm
	EAN	4251269328213	External diameter	75 mm
	Package quantity	5	Cut-out size, round	63,4 mm
	For max. no. of cables	14	Cut-out size, metric	M63
	Max. cable diameter	10,2 mm	Thread	M63 × 1,5
	Color	black	Thread length	14 mm
	Height	22 mm	(S)VOC tested	ja
			Clamping range	14 x 5 - 10.2 mm

KEL-DPZ 63 35 CR gy 	Part No.	43763.601	Mounting height	8 mm
	EAN	4251269328374	External diameter	75 mm
	Package quantity	5	Cut-out size, round	63,4 mm
	For max. no. of cables	35	Cut-out size, metric	M63
	Max. cable diameter	6,5 mm	Thread	M63 × 1,5
	Color	gray (similar RAL 7035)	Thread length	14 mm
	Height	22 mm	(S)VOC tested	nein
			Clamping range	35 x 3.2 - 6.5 mm

KEL-DPZ 63 35 CR (S)VOC gy 	Part No.	43763.600	Mounting height	8 mm
	EAN	4251269328060	External diameter	75 mm
	Package quantity	5	Cut-out size, round	63,4 mm
	For max. no. of cables	35	Cut-out size, metric	M63
	Max. cable diameter	6,5 mm	Thread	M63 × 1,5
	Color	gray (similar RAL 7035)	Thread length	14 mm
	Height	22 mm	(S)VOC tested	ja
			Clamping range	35 x 3.2 - 6.5 mm

KEL-DPZ 63 35 CR bk 	Part No.	50763.601	Mounting height	8 mm
	EAN	4251269328527	External diameter	75 mm
	Package quantity	5	Cut-out size, round	63,4 mm
	For max. no. of cables	35	Cut-out size, metric	M63
	Max. cable diameter	6,5 mm	Thread	M63 × 1,5
	Color	black	Thread length	14 mm
	Height	22 mm	(S)VOC tested	nein
			Clamping range	35 x 3.2 - 6.5 mm

KEL-DPZ 63 35 CR (S)VOC bk 	Part No.	50763.600	Mounting height	8 mm
	EAN	4251269328220	External diameter	75 mm
	Package quantity	5	Cut-out size, round	63,4 mm
	For max. no. of cables	35	Cut-out size, metric	M63
	Max. cable diameter	6,5 mm	Thread	M63 × 1,5
	Color	black	Thread length	14 mm
	Height	22 mm	(S)VOC tested	ja
			Clamping range	35 x 3.2 - 6.5 mm

