KT-DPF | Multi-range cable grommets, black

in pyramid shape, for cable diameters 3-26 mm / IP54



The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

Black KT-DPF grommets have an increased chemical resistance, e.g. against aggressive oils, coolants etc.

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

It is recommended that additional strain relief be provided for the cables using a cable tie.

Cutting of KT-DPF grommets: Cable diameter less 20%.

Advantages & Benefits

Specifications

Flame class UL94-HB Operating temperature -30 C° to 90 C	C°	
Flame class UL94-HB		
Material Elastomer	Easy storage	
IP rating (EN 60529) IP54	Large clamping range of 3 to 26 mm with only 3 gro Ideal for wiring non pre-terminated cables locally	mmets

Product Types & Sizes

T-DPF-A bk	Part No.	41360	Height	50 mm
	EAN	4251269307102	Mounting height	33 mm
	Package quantity	10	Clamping range	3 - 12 mm
	For max. no. of cables	1	Clamping range	1 x 3 - 12 mm
	Color	black		
	Length	21 mm		
	Width	21 mm		
IP54				
		41261	Usiaka	50
	Part No.	41361	Height	59 mm
	Part No. EAN	4251269307119	Mounting height	42 mm
	Part No.		=	
	Part No. EAN	4251269307119	Mounting height	42 mm
	Part No. EAN Package quantity	4251269307119 10	Mounting height For cable type	42 mm Round cable
IP54 CT-DPF-B bk	Part No. EAN Package quantity For max. no. of cables	4251269307119 10 1	Mounting height For cable type Clamping range	42 mm Round cable 4 - 18 mm



Part No. EAN Package quantity For max. no. of cables Color Length Width 41362 4251269307126 10 1 black 41,5 mm 42 mm Height Mounting height For cable type Clamping range Clamping range 59 mm 42 mm Round cable 14 - 26 mm 1 x 14 - 26 mm

