## **Bulkhead fittings & couplings**

for pneumatic hoses 4-12 mm



The bulkhead fittings & couplings for pneumatic hoses are also available individually, e.g. for use with the <u>AT-K-M</u> and <u>QT-AT-K-M</u> adapter grommets.

This means that pneumatic bulkhead couplings M12  $\times$  1.0 and M14  $\times$  1.0 can be integrated directly into the cable entry frame.

By utilising the adapter grommets AT-K-M, pneumatic bulkhead fittings & couplings can be integrated directly into the cable entry frame

RoHS

## **Specifications**

REACH

Material	Brass, nickel-plated
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free
Mounting options	Screw type mounting

## **Product Types & Sizes**

Bulkhead coupling D4



Part No.	99210
EAN	4251269325
	601
Package	10
quantity	
Thread	M12 × 1,0
Length	30,8 mm
For pneumatic	4 mm
hose	

**Advantages & Benefits** 

Space-saving solution

Separate cut-outs are no longer necessary



Part No.	99211
EAN	4251269325
	618
Package	10
quantity	
Thread	M14 × 1,0
Length	32,3 mm
For pneumatic	6 mm
hose	

## Bulkhead fitting D8



Part No.	99227
EAN	4251269332
	012
Package	10
quantity	
Thread	1/4"
Length	23 mm
For pneumatic	8 mm
hose	

Bulkhead fitting D10



Part No. FAN	99228 4251269332
	029
Package quantity	10
Thread	1/4"
Length	29,5 mm
For pneumatic	10 mm
hose	



Part No.	99229
EAN	4251269332
	036
Package	10
quantity	
Thread	1/4"
Length	31,5 mm
For pneumatic	12 mm
hose	

