

00 000 0000 00 가0 / IP65



KEL-DPR 24 2000 2400 2400 2400. 24 2000 2400 2400. 2400 2400 2400 2400. ST-B 2400 2400.

M4 □□□ □□□ □□□ □□□ □□□□ □□□ □□□ □ □□□□□ □□□ □ □□□□.



IP 6000 (EN 60529)	IP54, IP55, IP64, IP65
	6000 6000 6000
	UL94-V0, 6000
	-40 C° to 90 C°
	6000, 6000
6000	6000

11111


- 0000 000000 00 0000 00
- IP65 방수방진
- 00 00 00
- 00 00 00 00
- 00 00 0000 00
- 000000 M4 0000 0000 00 00 가

11 11 11 11

	EAN	46500		58 mm
		4251269335303		10,6 mm
		10	□□ □□	9,1 mm
□□□ □		12	□□ □□□	112 × 36 mm
□□ □□□ □□		15 mm	□□ □ □	4
			□□□ □□	5,8 mm
		147 mm	□□□ □□ □	12 x 1 - 15 mm

	EAN	46501 4251269335310			58 mm 10,6 mm
		10			9,1 mm
		17			112 × 36 mm
		12,6 mm			4
		147 mm			5,8 mm
					5 x 1 - 10.5 mm
					12 x 1 - 12.6 mm

	EAN	46502 4251269335327	10 25 12,1 mm	147 mm	58 mm 10,6 mm 9,1 mm 112 x 36 mm 4 5,8 mm 18 x 1 - 6.5 mm 7 x 1 - 12.1 mm
--	-----	------------------------	---------------------	--------	--




EAN
□□□ □
□□ □□□ □□

46503
4251269335334
10
26
16,1 mm

147 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□ □

58 mm
10,6 mm
9,1 mm
112 × 36 mm
4
5,8 mm
16 × 1 - 6.5 mm
4 × 1 - 12.1 mm
4 × 1 - 16.1 mm



EAN
□□□ □
□□ □□□ □□

46504
4251269335341
10
48
6,5 mm

147 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□ □

58 mm
10,6 mm
9,1 mm
112 × 36 mm
4
5,8 mm
48 × 1 - 6.5 mm