

□□ □□ 65 mm □□가□ / IP54 / UL Type 12



KEL-JUMBO □□□ □□□ □□□□ □□ □□ 65mm□ □□□ □□ □□, □□ □□□ □□ □□□ □□□□□.


○○○○ ○○○ ○○○ ○○○○ ○○○ ○○○ ○○가 가○○○○.

□□ □□ (Cut-out) □ □□□□. □□ □□ (Cut-out) □□ □□ □□ □□ +15 ~ 20%□□.

11 11

- 65mm 65mm 가
- 65mm 65mm 65mm 65mm 65mm 65mm
- 65mm 65mm 65mm 65mm 65mm 65mm
- EN 62444 65mm 65mm 65mm 65mm

IP 等级 (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
	密封型
	UL94-V0, 阻燃型
	-40 C° to 140 C°
	UV-照射, 冲击试验, 短路试验(V2A 钢), 耐腐蚀
尺寸	尺寸 见下
尺寸	35 mm



EAN


□□□ □

□□ □□□ □□

42360
4251269308550
1
1
65 mm
110 mm
116 mm

□□ □□
 □□ □□□
 □□ □ □
 □□□ □□
 □□□ □□
 □□□□ □□

35 mm
35 mm
78 × 80.5 mm
4
7 mm
□□□□ □
1 x KTF




EAN

□□□ □
□□ □□□ □□

42360.200
4251269308567
1
1
65 mm
110 mm
116 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□
□□□□ □□

35 mm
35 mm
78 × 80.5 mm
4
7 mm
□□□□□ (V2A)
1 x KTF




EAN

□□□ □
□□ □□□ □□

42350
4251269308536
1
2
65 mm
200 mm
116 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□
□□□□ □□

35 mm
35 mm
168 × 80.5 mm
4
7 mm
□□□□ □
2 x KTF



EAN

□□□ □
□□ □□□ □□

42350.200
4251269308543
1
2
65 mm
200 mm
116 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□
□□□□ □□

35 mm
35 mm
168 × 80.5 mm
4
7 mm
□□□□□□ (V2A)
2 x KTF