

# QT-AT-M | QT-AT-K-M adaptertulen

met binnendraad M5 - M25 / IP54



IP54

HL3  
EN 45545-2

ECOLAB  
certified

UV  
ISO 4892-2A

PNEUMATICS

RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany



WE  
CONTROL  
COMPONENTS

**Bestel direct online @ CC Nederland »**



**Voor aanvragen uit België [klik hier](#) »**

QT-AT-M is an adapter grommet (based on large QT grommets) with integrated metric threads.. The QT-AT-M adapter grommets are made of elastomer with a polyamide body. QT-AT-M adapter grommets are available with inner threads M12 x 1.0, M16 x 1.5, M20 x 1.5 and M25 x 1.5.

The QT-AT-M is ideal for creating an interface for signal, data, power or hybrid connectors by simply screwing them into the QT-AT-M thread. Pressure compensation elements or hose glands up to M25 x 1.5 can also be screwed into the QT-AT-M.

icotek also offers screw plugs for sizes M16, M20 and M25 to close the new adapter grommet with the metric internal thread QT-AT-M.

QT-AT-K-M is an adapter grommet (based on small QT grommets) with integrated metric threads, suitable for split icotek cable entry systems. The QT-AT-K-M adapter grommets are made of elastomer with a nickel-plated brass body. QT-AT-K-M adapter grommets are available with inner threads M5 x 0.5, M8 x 1.0, M12 x 1.0 and M12 x 1.5.

By using the QT-AT-K-M adapter grommet several connectors can be inserted directly into the cable entry frame e.g. pneumatic bulkhead connectors M12 x 1,0, metric connectors and pressure compensation elements.

They are compatible with all split [KEL-QUICK cable entry systems](#) (suitable for QT cable grommets).


## Specificaties


|                             |                                     |
|-----------------------------|-------------------------------------|
| IP-classificatie (EN 60529) | IP54                                |
| Materiaal                   | Elastomeer<br>Basisframe: Polyamide |
| Vlam klasse                 | UL94-V0, zelfdovend                 |
| Temperatuur                 | -40 C° tot 100 C°                   |
| Eigenschappen               | zonder siliconen, halogeenvrij      |

## Voordelen

- Connectoraansluitingen kunnen rechtstreeks in het kabelinvoersysteem worden geïntegreerd
- Aparte uitsparingen voor connectoren zijn niet meer nodig
- Ruimtebesparende oplossing


## Producttypes en maten

|                                                                                            |              |                      |                |             |
|--------------------------------------------------------------------------------------------|--------------|----------------------|----------------|-------------|
| <br>IP54 | Art.nr.      | <b>42604</b>         | Montage hoogte | <b>2 mm</b> |
|                                                                                            | EAN          | <b>4251269323423</b> |                |             |
|                                                                                            | Aantal       | <b>5</b>             |                |             |
|                                                                                            | Schroefdraad | <b>M5 x 0,5</b>      |                |             |
|                                                                                            | Lengte       | <b>20 mm</b>         |                |             |
|                                                                                            | Breedte      | <b>19 mm</b>         |                |             |
|                                                                                            | Hoogte       | <b>12 mm</b>         |                |             |




Art.nr. **42605**  
EAN **4251269323430**  
Aantal **5**  
Schroefdraad **M8 × 1,0**  
Lengte **20 mm**  
Breedte **19 mm**  
Hoogte **12 mm**

Montage hoogte **2 mm**




Art.nr. **42609**  
EAN **4251269323829**  
Aantal **5**  
Schroefdraad **M8 × 0,5**  
Lengte **20 mm**  
Breedte **19 mm**  
Hoogte **12 mm**

Montage hoogte **2 mm**




Art.nr. **42606**  
EAN **4251269323447**  
Aantal **5**  
Schroefdraad **M12 × 1,0**  
Lengte **20 mm**  
Breedte **19 mm**  
Hoogte **12 mm**

Montage hoogte **2 mm**




Art.nr. **42607**  
EAN **4251269323454**  
Aantal **5**  
Schroefdraad **M12 × 1,5**  
Lengte **20 mm**  
Breedte **19 mm**  
Hoogte **12 mm**

Montage hoogte **2 mm**




Art.nr. **42596**  
EAN **4251269322952**  
Aantal **10**  
Schroefdraad **M12 × 1,0**  
Lengte **40 mm**  
Breedte **39 mm**  
Hoogte **19**

Montage hoogte **2**




Art.nr. **42597**  
EAN **4251269322969**  
Aantal **10**  
Schroefdraad **M16 × 1,5**  
Lengte **40 mm**  
Breedte **39 mm**  
Hoogte **19**

Montage hoogte **2**



Art.nr. **42598**  
EAN **4251269322976**  
Aantal **10**  
Schroefdraad **M20 × 1,5**  
Lengte **40 mm**  
Breedte **39 mm**  
Hoogte **19**

Montage hoogte **2**



Art.nr.  
EAN  
Aantal  
Schroefdraad  
Lengte  
Breedte  
Hoogte

**42599**  
**4251269322983**  
**10**  
**M25 × 1,5**  
**40 mm**  
**39 mm**  
**19**

Montage hoogte

**2**

---

**icotek**<sup>®</sup>  
smart cable management