

Hydraulische handponzen

Hand hydraulische pons en accessoires



WE
CONTROL
COMPONENTS

Bestel direct online @ CC Nederland »



Voor aanvragen uit België [klik hier](#) »

Hand hydraulic punch driver

The compact, lightweight hand hydraulic punch driver makes it easy to punch holes into stainless V2A steel, mild steel, aluminium or plastics with a max. sheet thickness of 3 mm (V2A: 2 mm), due to its high hydraulic force. The cylinder of the punch driver rotates 360° on 3 axles, so maximum flexibility even in hard-to-reach places is provided.

The punch driver can be used with all icotek punches and also with punches of other manufacturers.

Scope of delivery:

- 1 hand hydraulic punch driver (weight: 2 kg)
- 1 draw stud $\varnothing$ 9.5 mm (3/8" UNF) to $\varnothing$ 19 mm (3/4" UNF), L: 105 mm
- 1 draw stud $\varnothing$ 19 mm (3/4" UNF), L: 130 mm
- 1 spacer
- 1 tube lubricant
- 1 HSS co-pilot drill (multi step drill)
- 1 robust plastic storage case
- Set PRO 16-31: 1 each knockout punch M16 | M20 | M25 | M32
- Set PRO 16-63: 1 each knockout punch M16 | M20 | M25 | M32 | M40 | M50 | M63

Hydraulic foot pump

Universally applicable single-stage foot pump with a fixed operating pressure of 450 bar and built-in pressure relief valve. Suitable for all icotek round punches, rectangular and square punches. Keeps your hands free to position the sheet metal punch precisely, especially when using larger sheet metal punches.

Scope of delivery:

- 1 foot pump
- 2,5 m high pressure hose including quick coupling
- 1 hydraulic cylinder for holding round and rectangular punch
- 1 draw stud for rectangular punch, Order No. 80209
- 1 draw stud for round punch (steel) M16 - M25,
- Order No. 80200
- 1 multi-step drill, Order No. 80204
- 1 spacer, Order No. 80202
- 1 tube lubricant, Order No. 80203

Note: storage case not included in delivery. Punch 125 x 125 mm (order no. 80063) is only to be used with hydraulic foot pump (order no. 80002). Please order draw stud (order no. 802139) and special nut (order no. 80214) as well.

Specificaties

Materiaal	Aluminium
------------------	-----------

Voordelen

- Maximale flexibiliteit dankzij 360 ° rotatie
- Compact, lichtgewicht aluminium ontwerp (2 kg) voor snelle en gemakkelijke bediening
- Hoge hydraulische kracht (60 kN, 600 bar) voor gemakkelijk ponsen
- Robuuste kunststof opbergkoffer
- Pons driver ook geschikt voor ponsen van andere fabrikanten

Producttypes en maten

Hydraulische voetspomp



Art.nr.	80002
EAN	425126932369
	0
Aantal	1
Ponskracht	60 kN
Bedrijfsdruk	450 bar



Art.nr.	80003
EAN	42512
	69332
	432
Aantal	1
Ponskr	60 kN
acht	
Bedrijf	600
sdruk	bar



Art.nr.	80000
EAN	42512
	69316
	135
Aantal	1
Ponskr	60 kN
acht	
Bedrijf	600
sdruk	bar



Art.nr. **80005**
 EAN **42512**
69316
142
 Aantal **1**
 Ponskr **60 kN**
 acht
 Bedrijf **600**
 sdruk **bar**



Art.nr. **80006**
 EAN **42512**
69316
159
 Aantal **1**
 Ponskr **60 kN**
 acht
 Bedrijf **600**
 sdruk **bar**

icotek[®]
 smart cable management